DU360H

	Static Pressure in Inches W.G.											
CFM	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750
	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
4500			334 8.0 / 0.73).
6500		307 7.2 / 0.61	368 9.7 / 1.05	422 12.4 / 1.54	474 15.1 / 2.10							12.
8500	315 8.3 / 0.53	366 10.4 / 1.00	416 12.5 / 1.53	463 14.8 / 2.10	506 16.9 / 2.71	547 19.2 / 3.36	587 22 / 4.06	626 25 / 4.82				97
10500	389 12.4 / 1.01	430 14.4 / 1.56	472 16.1 / 2.18	512 18.1 / 2.84	550 20 / 3.54	587 22 / 4.27	621 24 / 5.03	655 27 / 5.82	688 29 / 6.65	720 32 / 7.52	752 35 / 8.44	784 37 / 9.41
12500	463 17.1 / 1.70	498 18.9 / 2.34	533 21 / 3.05	567 22 / 3.80	601 24 / 4.59	634 26 / 5.41	665 28 / 6.25	696 31 / 7.13	725 33 / 8.02	754 35 / 8.95	782 37 / 9.90	
14500	537 22 / 2.65	567 24 / 3.39	597 26 / 4.18	627 28 / 5.02	657 30 / 5.89	686 32 / 6.81	715 34 / 7.74	743 36 / 8.71	770 37 / 9.69			
16500	611 28 / 3.90	637 30 / 4.74	664 33 / 5.62	690 34 / 6.54	717 36 / 7.51	743 38 / 8.50	769 39 / 9.53					
18500	685 35 / 5.49	709 37 / 6.43	732 40 / 7.40	756 42 / 8.42	779 43 / 9.47							2.
20500	759 43 / 7.47	780 45 / 8.50	802 46 / 9.58						-		14	
22500	833 50 / 9.88											

Max Sizeable RPM = 850 RPM. Table shown extended beyond this point for reference only.

Motor 00509ET3E254T-W22 has an rpm range of 300 to 850.

Motor 00709ET3E256T-W22 has an rpm range of 300 to 850.

Motor 00709ET3E256T-W22-50 has an rpm range of 300 to 730.

Motor 00712ET3H254T-W22 has an rpm range of 300 to 850.

Motor 01012ET3H256T-W22 has an rpm range of 300 to 850.

Motor DTP0036 has an rpm range of 300 to 850.

Motor DTP0056 has an rpm range of 300 to 850.

Motor DTP0104 has an rpm range of 438 to 850.

Motor DTP0104-50 has an rpm range of 438 to 850.

Motor DTP0106 has an rpm range of 300 to 850.

Motor DTP7/56 has an rpm range of 300 to 850.

Motor DTP7/56-50 has an rpm range of 300 to 850.

Motor GP0104 has an rpm range of 450 to 850.

Motor GP0104-50 has an rpm range of 360 to 850.

Motor GP7/54-50 has an rpm range of 360 to 850.

Motor NP7/56 has an rpm range of 300 to 850.

FloAire certifies that Model DU360H is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and 311 and comply with the requirements of the AMCA Certified Ratings Program. Tested to AMCA Standards 210 and 300. Meets California Energy Commission (CEC)

Performance shown is certified for Installation Type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances in the airstream.

The sound ratings shown are loudness values in hemispherical sones at 1.5m (5ft) in a hemispherical free field calculated per ANSI / AMCA Standard 301. Values shown are for installation type A: free inlet hemispherical sone levels.

Catalog #11 0F November 2024

