

F1-E.354-18Z

CFM	Static Pressure in Inches W.G.															
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500	3.750
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
800	575 / 0.04	622 / 0.05	815 / 0.12	971 / 0.19	1085 / 0.25	1192 / 0.32	1297 / 0.39	1404 / 0.48	1512 / 0.57	1619 / 0.68	1728 / 0.79	1831 / 0.92	1928 / 1.04	2015 / 1.17	2100 / 1.29	2180 / 1.43
1200	863 / 0.14	887 / 0.16	922 / 0.18	983 / 0.21	1137 / 0.32	1288 / 0.45	1390 / 0.56	1478 / 0.66	1554 / 0.75	1628 / 0.84	1700 / 0.94	1770 / 1.05	1840 / 1.15	1911 / 1.27	1980 / 1.38	2051 / 1.51
1600	1150 / 0.34	1167 / 0.35	1188 / 0.38	1212 / 0.40	1244 / 0.44	1290 / 0.48	1366 / 0.57	1501 / 0.74	1629 / 0.93	1726 / 1.09	1806 / 1.23	1878 / 1.37	1942 / 1.49	2003 / 1.62	2062 / 1.75	2116 / 1.87
2000	1438 / 0.66	1451 / 0.68	1465 / 0.70	1483 / 0.73	1500 / 0.76	1522 / 0.80	1548 / 0.84	1580 / 0.89	1621 / 0.96	1679 / 1.06	1767 / 1.22	1883 / 1.46	1990 / 1.70	2079 / 1.92	2153 / 2.11	2220 / 2.29
2400	1725 / 1.14	1737 / 1.17	1748 / 1.19	1761 / 1.22	1774 / 1.25	1788 / 1.29	1805 / 1.32	1822 / 1.37	1843 / 1.41	1866 / 1.47	1894 / 1.54	1926 / 1.61	1966 / 1.71	2019 / 1.84	2087 / 2.03	2176 / 2.27
2800	2013 / 1.81	2022 / 1.84	2032 / 1.87	2042 / 1.90	2053 / 1.94	2065 / 1.97	2077 / 2.01	2090 / 2.05	2104 / 2.10	2118 / 2.14	2134 / 2.19	2152 / 2.25	2172 / 2.32	2194 / 2.39	2219 / 2.47	2247 / 2.56

Max Sizeable RPM = 2900 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 320 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 320 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 320 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 320 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 320 to 2900.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 320 to 2900.