

F1-E.355-G10

CFM	Static Pressure in Inches W.G.					
	0.000	0.250	0.500	0.750	1.000	1.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
800			1198 / 0.26	1460 / 0.47	1681 / 0.71	1874 / 0.98
1000		954 / 0.13	1215 / 0.27	1468 / 0.47	1689 / 0.72	1883 / 1.00
1200	905 / 0.11	1061 / 0.18	1263 / 0.30	1485 / 0.49	1697 / 0.73	
1400	1055 / 0.18	1183 / 0.25	1344 / 0.36	1527 / 0.53	1716 / 0.76	
1600	1206 / 0.26	1315 / 0.34	1445 / 0.45	1595 / 0.61	1758 / 0.81	
1800	1356 / 0.37	1452 / 0.46	1561 / 0.57	1685 / 0.72	1824 / 0.91	
2000	1507 / 0.51	1591 / 0.60	1686 / 0.72	1792 / 0.86		
2200	1658 / 0.68	1734 / 0.78	1817 / 0.90			
2400	1809 / 0.88	1876 / 0.99				

Max Sizeable RPM = 1884 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-750I1-E-50-115 has an rpm range of 900 to 1800.

Motor BMN48-750I1-E-60-115 has an rpm range of 900 to 1800.

Motor BMN48-750I2-E-50-230/277 has an rpm range of 900 to 1800.

Motor BMN48-750I2-E-60-230/277 has an rpm range of 900 to 1800.