

F2-E.1004-20Z

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000	775 / 0.15	877 / 0.24	974 / 0.35	1063 / 0.47	1146 / 0.60	1225 / 0.74	1301 / 0.88	1376 / 1.02	1447 / 1.17	1517 / 1.33	1585 / 1.49	1650 / 1.65	1715 / 1.82
2500	968 / 0.29	1050 / 0.39	1132 / 0.53	1209 / 0.67	1281 / 0.82	1351 / 0.98	1416 / 1.14	1481 / 1.31	1543 / 1.47	1605 / 1.65	1664 / 1.83	1723 / 2.01	1781 / 2.20
3000	1161 / 0.49	1230 / 0.62	1299 / 0.77	1366 / 0.93	1431 / 1.10	1492 / 1.28	1552 / 1.46	1609 / 1.65	1665 / 1.84	1719 / 2.04	1773 / 2.24	1826 / 2.44	1877 / 2.65
3500	1355 / 0.78	1413 / 0.92	1472 / 1.09	1532 / 1.27	1589 / 1.46	1645 / 1.66	1698 / 1.86	1751 / 2.07	1802 / 2.29	1852 / 2.51	1900 / 2.73	1948 / 2.95	1994 / 3.18
4000	1549 / 1.17	1599 / 1.33	1652 / 1.51	1703 / 1.70	1754 / 1.91	1804 / 2.13	1854 / 2.35	1902 / 2.58	1948 / 2.82	1995 / 3.06	2040 / 3.30	2083 / 3.55	2127 / 3.80
4500	1741 / 1.66	1787 / 1.84	1833 / 2.04	1880 / 2.25	1926 / 2.47	1971 / 2.71	2016 / 2.95	2059 / 3.20	2103 / 3.45	2146 / 3.72	2187 / 3.98	2228 / 4.25	2268 / 4.52
5000	1935 / 2.28	1976 / 2.48	2017 / 2.69	2058 / 2.91	2101 / 3.16	2142 / 3.41	2182 / 3.66	2223 / 3.93	2263 / 4.21				
5500	2128 / 3.03	2165 / 3.25	2204 / 3.48	2241 / 3.72	2278 / 3.97								

Max Sizeable RPM = 2300 RPM. Table shown extended beyond this point for reference only.

Motor 186735/A01-ECM-50-240-20 has an rpm range of 300 to 2300.

Motor 186735/A01-ECM-60-240-20 has an rpm range of 300 to 2300.

Motor 186741/A01-ECM-50-480-20 has an rpm range of 300 to 2300.

Motor 186741/A01-ECM-60-480-20 has an rpm range of 300 to 2300.