

F2-E.452-22Z

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000	574 / 0.12	680 / 0.22	786 / 0.35	885 / 0.49	977 / 0.64	1062 / 0.81	1143 / 0.98	1220 / 1.16	1292 / 1.35	1361 / 1.54	1429 / 1.75	1493 / 1.95	1554 / 2.17
2500	717 / 0.23	801 / 0.36	888 / 0.50	973 / 0.67	1054 / 0.84	1130 / 1.02	1203 / 1.21	1273 / 1.41	1340 / 1.62	1405 / 1.83	1468 / 2.05	1528 / 2.28	1586 / 2.51
3000	860 / 0.39	929 / 0.54	1002 / 0.71	1074 / 0.89	1145 / 1.09	1214 / 1.29	1280 / 1.50	1343 / 1.72	1405 / 1.94	1465 / 2.18	1523 / 2.41	1580 / 2.66	1635 / 2.92
3500	1003 / 0.62	1062 / 0.79	1124 / 0.98	1186 / 1.19	1248 / 1.40	1309 / 1.62	1369 / 1.86	1427 / 2.10	1484 / 2.34	1539 / 2.59	1593 / 2.85	1646 / 3.12	1697 / 3.39
4000	1147 / 0.92	1198 / 1.12	1251 / 1.33	1305 / 1.56	1360 / 1.79	1414 / 2.03	1468 / 2.29	1521 / 2.55	1573 / 2.81	1624 / 3.09	1674 / 3.37	1723 / 3.65	1771 / 3.94
4500	1290 / 1.31	1335 / 1.53	1382 / 1.77	1430 / 2.01	1478 / 2.27	1527 / 2.53	1576 / 2.81	1624 / 3.09	1671 / 3.37	1718 / 3.67	1764 / 3.97	1809 / 4.27	1854 / 4.59
5000	1433 / 1.80	1473 / 2.04	1516 / 2.30	1558 / 2.56	1602 / 2.84	1645 / 3.13	1689 / 3.42	1733 / 3.73	1776 / 4.03	1820 / 4.35	1862 / 4.67		
5500	1577 / 2.40	1613 / 2.66	1651 / 2.94	1690 / 3.23	1728 / 3.52	1768 / 3.83	1808 / 4.15	1848 / 4.47					
6000	1720 / 3.11	1753 / 3.40	1788 / 3.70	1823 / 4.01	1858 / 4.32								
6500	1864 / 3.96												

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 300 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 300 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 300 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 300 to 1870.