

F3-D.500-24D

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3500			851 / 1.19	921 / 1.46	983 / 1.74	1041 / 2.02	1094 / 2.30	1145 / 2.59	1192 / 2.89	1238 / 3.20	1281 / 3.51	1322 / 3.83	1363 / 4.16	1402 / 4.49	1439 / 4.83
4000		861 / 1.29	932 / 1.59	998 / 1.90	1057 / 2.21	1112 / 2.52	1163 / 2.84	1212 / 3.16	1258 / 3.49	1302 / 3.82	1344 / 4.16	1385 / 4.51	1423 / 4.86	1461 / 5.21	1498 / 5.58
4500	879 / 1.41	950 / 1.74	1016 / 2.08	1077 / 2.43	1133 / 2.78	1186 / 3.13	1235 / 3.48	1282 / 3.83	1327 / 4.19	1369 / 4.55	1410 / 4.92	1450 / 5.30	1488 / 5.67	1524 / 6.06	1560 / 6.45
5000	976 / 1.94	1041 / 2.30	1102 / 2.68	1159 / 3.06	1212 / 3.45	1262 / 3.83	1310 / 4.22	1355 / 4.61	1397 / 5.00	1439 / 5.40	1479 / 5.80	1517 / 6.20	1554 / 6.61	1590 / 7.03	1625 / 7.44
5500	1074 / 2.58	1133 / 2.98	1189 / 3.39	1243 / 3.81	1293 / 4.23	1341 / 4.66	1386 / 5.08	1429 / 5.50	1471 / 5.93	1511 / 6.36	1550 / 6.80	1587 / 7.23	1623 / 7.67	1658 / 8.12	1692 / 8.57
6000	1171 / 3.35	1226 / 3.78	1278 / 4.23	1328 / 4.69	1376 / 5.14	1421 / 5.60	1465 / 6.07	1506 / 6.53	1546 / 6.99	1585 / 7.46	1622 / 7.93	1659 / 8.40	1694 / 8.87	1728 / 9.35	1761 / 9.82
6500	1269 / 4.26	1320 / 4.73	1368 / 5.21	1415 / 5.70	1460 / 6.20	1504 / 6.69	1545 / 7.19	1585 / 7.69	1624 / 8.20	1661 / 8.70	1697 / 9.20	1732 / 9.71			
7000	1367 / 5.32	1414 / 5.82	1459 / 6.34	1503 / 6.86	1546 / 7.40	1587 / 7.93	1627 / 8.47	1665 / 9.01	1703 / 9.55						
7500	1464 / 6.54	1508 / 7.08	1551 / 7.63	1593 / 8.19	1633 / 8.76	1673 / 9.33	1710 / 9.90								
8000	1561 / 7.93	1603 / 8.51	1644 / 9.10	1683 / 9.70											

Max Sizeable RPM = 2000 RPM. Table shown extended beyond this point for reference only.

- Motor 00318ET3H182T-W22 has an rpm range of 800 to 1750.
- Motor 00318OT3H182T-S has an rpm range of 800 to 1750.
- Motor 00512ET3E215T-W22 has an rpm range of 800 to 1150.
- Motor 00512OT3H215T-S has an rpm range of 800 to 1150.
- Motor 00518ET3H184T-W22 has an rpm range of 800 to 1750.
- Motor 00518OT3H184T-S has an rpm range of 800 to 1750.
- Motor 00718OT3H213T-S has an rpm range of 800 to 1750.
- Motor 01018OT3H215T-S has an rpm range of 800 to 1750.
- Motor DHP0056 has an rpm range of 800 to 1165.
- Motor DP010504NPW01 has an rpm range of 800 to 1750.
- Motor DTP0026 has an rpm range of 800 to 1150.
- Motor DTP0034 has an rpm range of 800 to 1755.
- Motor DTP0034-50HZ has an rpm range of 800 to 1438.
- Motor DTP0036 has an rpm range of 800 to 1150.
- Motor DTP0054 has an rpm range of 800 to 1750.
- Motor DTP0054-50 has an rpm range of 800 to 1435.
- Motor DTP0056 has an rpm range of 800 to 1150.
- Motor DTP0104 has an rpm range of 800 to 1755.
- Motor DTP0104-50 has an rpm range of 800 to 1436.
- Motor DTP7/54 has an rpm range of 800 to 1750.
- Motor DTP7/54-50 has an rpm range of 800 to 1470.
- Motor GP0034 has an rpm range of 800 to 1800.
- Motor GP0034-50 has an rpm range of 800 to 1440.
- Motor GP0054 has an rpm range of 800 to 1800.
- Motor GP0054-50 has an rpm range of 800 to 1440.
- Motor GP0056 has an rpm range of 800 to 1150.
- Motor GP0104 has an rpm range of 800 to 1755.
- Motor GP0104-50 has an rpm range of 800 to 1440.
- Motor NP0056 has an rpm range of 800 to 1150.

Max listed CFM for Recirculating Direct Fired Heaters : A3 = 6500