

F76

| CFM | Static Pressure in Inches W.G. | | | | | | | | | |
|------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | 0.000 | 0.125 | 0.250 | 0.375 | 0.500 | 0.625 | 0.750 | 0.875 | 1.000 | 1.125 |
| | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP |
| 600 | | 924 / 0.09 | 1068 / 0.12 | 1193 / 0.15 | 1307 / 0.18 | 1408 / 0.21 | 1504 / 0.24 | 1587 / 0.27 | 1671 / 0.31 | 1749 / 0.34 |
| 700 | 855 / 0.10 | 1028 / 0.14 | 1161 / 0.17 | 1277 / 0.20 | 1383 / 0.24 | 1483 / 0.27 | 1573 / 0.31 | 1659 / 0.34 | 1741 / 0.38 | |
| 800 | 977 / 0.14 | 1136 / 0.19 | 1258 / 0.23 | 1368 / 0.27 | 1468 / 0.31 | 1562 / 0.34 | 1649 / 0.38 | 1732 / 0.42 | | |
| 900 | 1099 / 0.20 | 1247 / 0.26 | 1360 / 0.30 | 1461 / 0.35 | 1557 / 0.39 | 1636 / 0.43 | 1731 / 0.48 | | | |
| 1000 | 1221 / 0.28 | 1359 / 0.34 | 1464 / 0.39 | 1560 / 0.44 | 1650 / 0.49 | 1736 / 0.54 | | | | |
| 1100 | 1343 / 0.37 | 1473 / 0.44 | 1574 / 0.50 | 1664 / 0.56 | 1749 / 0.61 | | | | | |
| 1200 | 1465 / 0.48 | 1585 / 0.56 | 1683 / 0.63 | 1655 / 0.61 | | | | | | |
| 1300 | 1587 / 0.61 | 1702 / 0.70 | 1793 / 0.77 | | | | | | | |
| 1400 | 1709 / 0.76 | | | | | | | | | |

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-750I1-E-50-115 has an rpm range of 800 to 1800.

Motor BMN48-750I1-E-60-115 has an rpm range of 800 to 1800.

Motor BMN48-750I2-E-60-230/277 has an rpm range of 800 to 1800.