FSIF24DD

	Static Pressure in Inches W.G.							
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500
СЕМ	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
2700			757 14.5 / 1.07	899 19.0 / 1.70	1025 23 / 2.41	1140 28 / 3.19	1244 32 / 4.03	1341 36 / 4.92
4700		767 14.9 / 1.17	905 19.2 / 1.93	1021 23 / 2.74	1125 27 / 3.62	1221 31 / 4.56	1312 35 / 5.55	
6700	852 18.0 / 1.39	972 22 / 2.33	1090 26 / 3.36	1193 30 / 4.42	1285 34 / 5.52			
8700	1106 27 / 3.04	1197 30 / 4.22	1292 34 / 5.51					

Max Sizeable RPM = 1350 RPM. Table shown extended beyond this point for reference only.

Motor DTP0056 has an rpm range of 600 to 1150.

Motor DTP0056-50 has an rpm range of 600 to 958.

Motor DTP0104 has an rpm range of 600 to 1350.

Motor DTP0104-50 has an rpm range of 600 to 1350.

Motor DTP0154 has an rpm range of 600 to 1350.

Motor DTP0154-50 has an rpm range of 600 to 1350.

Motor DTP7/54 has an rpm range of 600 to 1350.

Motor DTP7/54-50 has an rpm range of 600 to 1350.

FloAire certifies that the FSIF24DD shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and 311 and complies with the requirements of the AMCA Certified Ratings Program. Tested to AMCA Standards 210 and 300. Meets California Energy Commission (CEC) Title 20 Regulations.

Performance shown is certified for Installation Type B: Free inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances in the airstream. Power rating (BHP) includes transmission losses.

The sound ratings shown are loudness values in hemispherical sones at 1.5m (5ft) in a hemispherical free field calculated per ANSI/AMCA Standard 301. Values shown are for installation type B: free inlet hemispherical sone levels. Ratings do not not include the effect of duct end correction.

Catalog #110F November 2024

