

RTU1-15-FA

CFM	Static Pressure in Inches W.G.															
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500	3.750
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
500			801 / 0.14	978 / 0.24	1124 / 0.35	1250 / 0.47	1366 / 0.59	1471 / 0.73								
750			807 / 0.16	984 / 0.28	1135 / 0.40	1267 / 0.54	1384 / 0.68	1491 / 0.84	1592 / 1.00	1685 / 1.17	1773 / 1.35	1856 / 1.53	1938 / 1.72	2011 / 1.90	2083 / 2.10	2155 / 2.31
1000			835 / 0.20	994 / 0.32	1139 / 0.45	1271 / 0.60	1391 / 0.76	1502 / 0.93	1603 / 1.11	1701 / 1.30	1789 / 1.49	1876 / 1.70	1957 / 1.90	2033 / 2.11	2105 / 2.32	2179 / 2.55
1250			897 / 0.25	1028 / 0.37	1156 / 0.51	1279 / 0.66	1397 / 0.84	1506 / 1.02	1609 / 1.21	1705 / 1.41	1796 / 1.62	1883 / 1.84	1965 / 2.06	2042 / 2.29	2119 / 2.52	2193 / 2.77
1500		865 / 0.21	979 / 0.32	1089 / 0.44	1199 / 0.59	1307 / 0.75	1414 / 0.92	1515 / 1.11	1615 / 1.31	1708 / 1.52	1799 / 1.74	1887 / 1.97	1969 / 2.21	2049 / 2.45	2125 / 2.70	2199 / 2.96
1750	807 / 0.15	971 / 0.28	1073 / 0.41	1168 / 0.54	1263 / 0.69	1357 / 0.85	1450 / 1.03	1543 / 1.23	1634 / 1.43	1722 / 1.65	1810 / 1.87	1892 / 2.11	1973 / 2.35	2052 / 2.61	2129 / 2.87	
2000	923 / 0.23	1079 / 0.38	1173 / 0.52	1259 / 0.67	1342 / 0.82	1423 / 0.99	1507 / 1.18	1589 / 1.37	1671 / 1.58	1751 / 1.79	1832 / 2.03	1910 / 2.27	1988 / 2.52	2062 / 2.77	2137 / 3.05	
2250	1038 / 0.32	1189 / 0.50	1277 / 0.66	1356 / 0.82	1431 / 0.99	1505 / 1.16	1579 / 1.35	1652 / 1.55	1725 / 1.76	1799 / 1.98	1870 / 2.21	1943 / 2.46	2014 / 2.71	2085 / 2.98	2155 / 3.25	
2500	1153 / 0.44	1299 / 0.65	1384 / 0.82	1458 / 1.00	1527 / 1.18	1594 / 1.36	1661 / 1.56	1728 / 1.77	1793 / 1.98	1859 / 2.21	1925 / 2.44	1990 / 2.69	2056 / 2.95	2120 / 3.21	2185 / 3.49	
2750	1268 / 0.59	1411 / 0.83	1492 / 1.02	1562 / 1.21	1627 / 1.40	1690 / 1.60	1752 / 1.81	1812 / 2.02	1872 / 2.24	1933 / 2.48	1991 / 2.71	2052 / 2.97	2112 / 3.23	2170 / 3.49		
3000	1384 / 0.76	1523 / 1.03	1601 / 1.24	1668 / 1.45	1730 / 1.66	1789 / 1.87	1846 / 2.09	1902 / 2.31	1958 / 2.54	2013 / 2.78	2069 / 3.03	2123 / 3.29	2179 / 3.55			

Max Sizeable RPM = 2200 RPM. Table shown extended beyond this point for reference only.

Motor 00158ET3H145T-W22 has an rpm range of 800 to 1750.

Motor 00158OT3H145T-S has an rpm range of 800 to 1750.

Motor 00212OT3H184T-S has an rpm range of 800 to 1150.

Motor 00218ET3H145T-W22 has an rpm range of 800 to 1750.

Motor 00218OT3H145T-S has an rpm range of 800 to 1750.

Motor 00536OT3H182T-S has an rpm range of 900 to 2200.

Motor BMN145-2.0I2-CS-UB1-50 (1200RPM) has an rpm range of 800 to 1200.

Motor BMN145-2.0I2-CS-UB1-60 (1200RPM) has an rpm range of 800 to 1200.

Motor BMN145-2.0I2-ES-UB1-50 (1800RPM) has an rpm range of 800 to 1800.

Motor BMN145-2.0I2-ES-UB1-60 (1800RPM) has an rpm range of 800 to 1800.

Motor DTP0022 has an rpm range of 900 to 2200.

Motor DTP0024 has an rpm range of 800 to 1740.

Motor DTP0024-50HZ has an rpm range of 800 to 1415.

Motor DTP0032 has an rpm range of 900 to 2200.

Motor DTP0034 has an rpm range of 800 to 1755.

Motor DTP0034-50HZ has an rpm range of 800 to 1438.

Motor DTP0054 has an rpm range of 800 to 1750.

Motor DTP0054-50 has an rpm range of 800 to 1435.

Motor DTP1/54 has an rpm range of 800 to 1750.

Motor DTP1/54-50HZ has an rpm range of 800 to 1426.

Motor GP0024 has an rpm range of 800 to 1740.

Motor GP0024-50 has an rpm range of 800 to 1440.

Motor GP1/54 has an rpm range of 800 to 1800.

Motor GP1/54-50 has an rpm range of 800 to 1440.

Motor NP0024 has an rpm range of 800 to 1740.