

RTU1-18-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000	
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	
500			1094 / 0.21	1330 / 0.35	1529 / 0.51	1701 / 0.68	1859 / 0.87	2008 / 1.07	2146 / 1.28	2273 / 1.50	2392 / 1.73	2513 / 1.98	2618 / 2.21	
750		815 / 0.12	1116 / 0.26	1351 / 0.43	1550 / 0.62	1724 / 0.81	1884 / 1.03	2027 / 1.25	2161 / 1.48	2294 / 1.73	2412 / 1.98	2525 / 2.24	2641 / 2.53	
1000		864 / 0.15	1144 / 0.32	1376 / 0.51	1572 / 0.72	1748 / 0.95	1905 / 1.18	2049 / 1.43	2188 / 1.70	2315 / 1.96	2433 / 2.24	2551 / 2.54	2660 / 2.83	
1250		935 / 0.19	1185 / 0.38	1404 / 0.59	1598 / 0.83	1771 / 1.08	1929 / 1.35	2073 / 1.62	2208 / 1.90	2336 / 2.20	2456 / 2.50	2572 / 2.82	2682 / 3.15	
1500		1023 / 0.23	1243 / 0.44	1445 / 0.68	1630 / 0.94	1799 / 1.21	1953 / 1.50	2098 / 1.81	2232 / 2.12	2358 / 2.44	2479 / 2.77	2595 / 3.12		
1750	910 / 0.12	1123 / 0.30	1316 / 0.52	1500 / 0.77	1671 / 1.05	1834 / 1.35	1984 / 1.67	2126 / 2.00	2258 / 2.33	2384 / 2.68	2504 / 3.04	2616 / 3.40		
2000	1040 / 0.17	1229 / 0.37	1402 / 0.61	1567 / 0.88	1727 / 1.18	1878 / 1.50	2022 / 1.84	2157 / 2.18	2288 / 2.55	2413 / 2.92	2528 / 3.30	2642 / 3.70		
2250	1169 / 0.24	1341 / 0.47	1497 / 0.72	1647 / 1.01	1793 / 1.32	1933 / 1.66	2070 / 2.02	2199 / 2.38	2324 / 2.77	2446 / 3.17	2560 / 3.57	2672 / 4.00		
2500	1299 / 0.34	1456 / 0.58	1598 / 0.85	1735 / 1.15	1870 / 1.49	2000 / 1.84	2128 / 2.21	2250 / 2.60	2370 / 3.00	2485 / 3.42	2596 / 3.85			
2750	1429 / 0.45	1573 / 0.71	1705 / 1.01	1831 / 1.32	1955 / 1.67	2075 / 2.04	2195 / 2.43	2309 / 2.83	2423 / 3.25	2535 / 3.70	2642 / 4.15			
3000	1558 / 0.58	1692 / 0.87	1815 / 1.18	1932 / 1.52	2046 / 1.88	2158 / 2.26	2269 / 2.66	2379 / 3.09	2486 / 3.53	2591 / 3.99	2693 / 4.46			

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 800 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 800 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 800 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 800 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 800 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 800 to 2700.