

# RTU1-E.104-16-FA

CFM	Static Pressure in Inches W.G.										
	0.000	0.625	1.250	1.875	2.500	3.125	3.750	4.375	5.000	5.625	6.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
500			1337 / 0.22	1623 / 0.34	1873 / 0.48	2083 / 0.63	2283 / 0.81	2463 / 1.01	2632 / 1.23	2793 / 1.48	2941 / 1.75
750		1029 / 0.12	1374 / 0.30	1652 / 0.48	1894 / 0.66	2107 / 0.83	2301 / 1.02	2483 / 1.21	2650 / 1.41	2809 / 1.63	2953 / 1.84
1000		1125 / 0.14	1437 / 0.34	1701 / 0.57	1931 / 0.82	2141 / 1.06	2331 / 1.30	2506 / 1.53	2674 / 1.77	2825 / 2.00	2976 / 2.25
1250		1248 / 0.19	1523 / 0.37	1766 / 0.62	1984 / 0.91	2185 / 1.22	2372 / 1.52	2541 / 1.82	2706 / 2.12	2854 / 2.41	
1500	1115 / 0.12	1388 / 0.27	1630 / 0.43	1852 / 0.67	2058 / 0.98	2246 / 1.31	2423 / 1.67	2591 / 2.03	2747 / 2.39	2896 / 2.75	
1750	1301 / 0.19	1539 / 0.38	1755 / 0.53	1957 / 0.75	2147 / 1.04	2324 / 1.38	2493 / 1.76	2652 / 2.16	2804 / 2.58	2946 / 2.99	
2000	1487 / 0.29	1699 / 0.51	1892 / 0.67	2077 / 0.88	2250 / 1.14	2415 / 1.47	2574 / 1.85	2725 / 2.26	2874 / 2.71		
2250	1673 / 0.41	1863 / 0.68	2040 / 0.86	2208 / 1.06	2346 / 1.26	2520 / 1.60	2672 / 1.97	2812 / 2.37	2953 / 2.82		
2500	1859 / 0.56	2031 / 0.88	2193 / 1.09	2347 / 1.29	2495 / 1.52	2640 / 1.81	2778 / 2.14	2914 / 2.53			
2750	2045 / 0.75	2202 / 1.12	2352 / 1.36	2493 / 1.57	2632 / 1.80	2767 / 2.07	2898 / 2.39				
3000	2230 / 0.97	2375 / 1.39	2515 / 1.68	2648 / 1.91	2775 / 2.14	2901 / 2.40					

Max Sizeable RPM = 3000 RPM. Table shown extended beyond this point for reference only.

Motor 186725/A01-ECM-50-277-16 has an rpm range of 1000 to 2390.

Motor 186725/A01-ECM-60-277-16 has an rpm range of 1000 to 2390.

Motor 186727/A01-ECM-50-480-16 has an rpm range of 1000 to 3000.

Motor 186727/A01-ECM-60-480-16 has an rpm range of 1000 to 3000.

Motor 186728/A01-ECM-50-240-16 has an rpm range of 1000 to 2770.

Motor 186728/A01-ECM-60-240-16 has an rpm range of 1000 to 2770.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 1000 to 2700.