

RTU1-E.302-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
900			1146 / 0.31	1376 / 0.49	1573 / 0.69	1748 / 0.91	1907 / 1.14	2050 / 1.37	2184 / 1.62	2314 / 1.89	2432 / 2.15	2550 / 2.44	2663 / 2.74
1110		919 / 0.18	1183 / 0.36	1407 / 0.57	1599 / 0.79	1770 / 1.03	1927 / 1.27	2071 / 1.53	2207 / 1.81	2332 / 2.09	2456 / 2.39	2569 / 2.69	2681 / 3.00
1320		991 / 0.22	1229 / 0.42	1441 / 0.65	1630 / 0.89	1798 / 1.15	1953 / 1.42	2095 / 1.70	2230 / 2.00	2357 / 2.31	2477 / 2.62	2588 / 2.93	2699 / 3.27
1530		1073 / 0.27	1288 / 0.49	1485 / 0.74	1665 / 1.00	1830 / 1.28	1982 / 1.57	2122 / 1.88	2257 / 2.20	2383 / 2.53	2500 / 2.86	2615 / 3.21	
1740	960 / 0.15	1163 / 0.34	1355 / 0.57	1538 / 0.83	1709 / 1.12	1867 / 1.42	2016 / 1.73	2153 / 2.06	2286 / 2.40	2410 / 2.75	2525 / 3.10	2640 / 3.48	
1950	1076 / 0.21	1258 / 0.42	1433 / 0.67	1601 / 0.94	1760 / 1.24	1912 / 1.56	2055 / 1.90	2189 / 2.24	2319 / 2.61	2441 / 2.98	2556 / 3.36	2668 / 3.75	
2160	1191 / 0.29	1357 / 0.51	1516 / 0.77	1671 / 1.07	1820 / 1.38	1964 / 1.72	2099 / 2.07	2215 / 2.40	2356 / 2.83	2474 / 3.22	2587 / 3.62	2697 / 4.03	
2370	1307 / 0.38	1458 / 0.62	1605 / 0.90	1748 / 1.21	1887 / 1.54	2020 / 1.89	2151 / 2.26	2277 / 2.65	2396 / 3.05	2513 / 3.47	2625 / 3.89		
2580	1423 / 0.49	1563 / 0.75	1697 / 1.05	1830 / 1.37	1959 / 1.71	2086 / 2.08	2209 / 2.47	2329 / 2.88	2445 / 3.30	2557 / 3.73	2665 / 4.17		
2790	1539 / 0.63	1669 / 0.90	1794 / 1.21	1918 / 1.55	2038 / 1.91	2158 / 2.30	2274 / 2.70	2387 / 3.12	2498 / 3.56	2605 / 4.00			
3000	1655 / 0.78	1775 / 1.07	1893 / 1.40	2008 / 1.75	2122 / 2.13	2234 / 2.53	2344 / 2.95	2451 / 3.38	2558 / 3.84	2662 / 4.31			

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.