

RTU1-E.304-18-FA

| CFM | Static Pressure in Inches W.G. | | | | | | | | | | | | |
|------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | 0.000 | 0.500 | 1.000 | 1.500 | 2.000 | 2.500 | 3.000 | 3.500 | 4.000 | 4.500 | 5.000 | 5.500 | 6.000 |
| | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP |
| 900 | | | 1146 / 0.31 | 1376 / 0.49 | 1573 / 0.69 | 1748 / 0.91 | 1907 / 1.14 | 2050 / 1.37 | 2184 / 1.62 | 2314 / 1.89 | 2432 / 2.15 | 2550 / 2.44 | 2663 / 2.74 |
| 1110 | | 919 / 0.18 | 1183 / 0.36 | 1407 / 0.57 | 1599 / 0.79 | 1770 / 1.03 | 1927 / 1.27 | 2071 / 1.53 | 2207 / 1.81 | 2332 / 2.09 | 2456 / 2.39 | 2569 / 2.69 | 2681 / 3.00 |
| 1320 | | 991 / 0.22 | 1229 / 0.42 | 1441 / 0.65 | 1630 / 0.89 | 1798 / 1.15 | 1953 / 1.42 | 2095 / 1.70 | 2230 / 2.00 | 2357 / 2.31 | 2477 / 2.62 | 2588 / 2.93 | 2699 / 3.27 |
| 1530 | | 1073 / 0.27 | 1288 / 0.49 | 1485 / 0.74 | 1665 / 1.00 | 1830 / 1.28 | 1982 / 1.57 | 2122 / 1.88 | 2257 / 2.20 | 2383 / 2.53 | 2500 / 2.86 | 2615 / 3.21 | |
| 1740 | 960 / 0.15 | 1163 / 0.34 | 1355 / 0.57 | 1538 / 0.83 | 1709 / 1.12 | 1867 / 1.42 | 2016 / 1.73 | 2153 / 2.06 | 2286 / 2.40 | 2410 / 2.75 | 2525 / 3.10 | 2640 / 3.48 | |
| 1950 | 1076 / 0.21 | 1258 / 0.42 | 1433 / 0.67 | 1601 / 0.94 | 1760 / 1.24 | 1912 / 1.56 | 2055 / 1.90 | 2189 / 2.24 | 2319 / 2.61 | 2441 / 2.98 | 2556 / 3.36 | 2668 / 3.75 | |
| 2160 | 1191 / 0.29 | 1357 / 0.51 | 1516 / 0.77 | 1671 / 1.07 | 1820 / 1.38 | 1964 / 1.72 | 2099 / 2.07 | 2215 / 2.40 | 2356 / 2.83 | 2474 / 3.22 | 2587 / 3.62 | 2697 / 4.03 | |
| 2370 | 1307 / 0.38 | 1458 / 0.62 | 1605 / 0.90 | 1748 / 1.21 | 1887 / 1.54 | 2020 / 1.89 | 2151 / 2.26 | 2277 / 2.65 | 2396 / 3.05 | 2513 / 3.47 | 2625 / 3.89 | | |
| 2580 | 1423 / 0.49 | 1563 / 0.75 | 1697 / 1.05 | 1830 / 1.37 | 1959 / 1.71 | 2086 / 2.08 | 2209 / 2.47 | 2329 / 2.88 | 2445 / 3.30 | 2557 / 3.73 | 2665 / 4.17 | | |
| 2790 | 1539 / 0.63 | 1669 / 0.90 | 1794 / 1.21 | 1918 / 1.55 | 2038 / 1.91 | 2158 / 2.30 | 2274 / 2.70 | 2387 / 3.12 | 2498 / 3.56 | 2605 / 4.00 | | | |
| 3000 | 1655 / 0.78 | 1775 / 1.07 | 1893 / 1.40 | 2008 / 1.75 | 2122 / 2.13 | 2234 / 2.53 | 2344 / 2.95 | 2451 / 3.38 | 2558 / 3.84 | 2662 / 4.31 | | | |

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.