

RTU1-E.402-11-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100				1897 / 0.61	2011 / 0.73	2115 / 0.86	2213 / 0.99	2306 / 1.12	2397 / 1.25
1170			1851 / 0.54	1973 / 0.68	2082 / 0.81	2187 / 0.95	2281 / 1.08	2373 / 1.22	
1240			1928 / 0.61	2050 / 0.75	2160 / 0.90	2259 / 1.04	2348 / 1.18		
1310		1877 / 0.53	2009 / 0.68	2127 / 0.83	2235 / 0.99	2331 / 1.14			
1380	1821 / 0.48	1960 / 0.60	2091 / 0.76	2208 / 0.93	2312 / 1.09				
1450	1913 / 0.55	2048 / 0.69	2174 / 0.85	2287 / 1.02	2389 / 1.19				
1520	2005 / 0.64	2135 / 0.78	2255 / 0.94	2364 / 1.12					
1590	2098 / 0.73	2221 / 0.87	2338 / 1.05						
1660	2190 / 0.83	2309 / 0.98							
1730	2282 / 0.94	2396 / 1.09							
1800	2375 / 1.06								

Max Sizeable RPM = 2400 RPM. Table shown extended beyond this point for reference only.

Motor DTP0022 has an rpm range of 1800 to 2400.

Motor DTP0032 has an rpm range of 1800 to 2400.