

RTU1-E.454-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1300		983 / 0.22	1225 / 0.42	1438 / 0.64	1627 / 0.88	1796 / 1.14	1952 / 1.41	2093 / 1.69	2230 / 1.99	2355 / 2.29	2476 / 2.60	2590 / 2.92	2697 / 3.24
1470		1049 / 0.26	1269 / 0.47	1471 / 0.71	1655 / 0.97	1822 / 1.25	1971 / 1.52	2115 / 1.83	2248 / 2.14	2375 / 2.46	2492 / 2.78	2606 / 3.13	
1640	905 / 0.13	1119 / 0.31	1323 / 0.53	1512 / 0.78	1687 / 1.06	1849 / 1.35	2000 / 1.66	2138 / 1.97	2271 / 2.30	2394 / 2.64	2515 / 2.99	2628 / 3.35	
1810	998 / 0.17	1194 / 0.36	1381 / 0.60	1558 / 0.87	1725 / 1.16	1881 / 1.47	2029 / 1.79	2165 / 2.12	2294 / 2.46	2420 / 2.83	2535 / 3.19	2646 / 3.56	
1980	1092 / 0.22	1272 / 0.43	1444 / 0.68	1610 / 0.96	1768 / 1.26	1919 / 1.59	2060 / 1.92	2195 / 2.28	2324 / 2.64	2444 / 3.01	2561 / 3.40	2672 / 3.79	
2150	1186 / 0.29	1352 / 0.51	1512 / 0.77	1667 / 1.06	1817 / 1.38	1960 / 1.71	2098 / 2.07	2228 / 2.44	2352 / 2.81	2471 / 3.20	2587 / 3.61	2698 / 4.02	
2320	1280 / 0.36	1434 / 0.60	1584 / 0.87	1729 / 1.17	1869 / 1.50	2007 / 1.85	2138 / 2.22	2266 / 2.61	2387 / 3.00	2503 / 3.41	2616 / 3.83		
2490	1373 / 0.44	1518 / 0.70	1658 / 0.98	1793 / 1.29	1927 / 1.64	2058 / 2.00	2184 / 2.38	2306 / 2.78	2425 / 3.20	2538 / 3.62	2646 / 4.05		
2660	1467 / 0.54	1602 / 0.81	1734 / 1.11	1863 / 1.44	1990 / 1.79	2113 / 2.16	2233 / 2.56	2350 / 2.97	2465 / 3.40	2575 / 3.83	2681 / 4.28		
2830	1561 / 0.65	1689 / 0.93	1812 / 1.25	1934 / 1.59	2054 / 1.95	2172 / 2.34	2286 / 2.74	2398 / 3.17	2509 / 3.61	2616 / 4.06			
3000	1655 / 0.78	1775 / 1.07	1893 / 1.40	2008 / 1.75	2122 / 2.13	2234 / 2.53	2344 / 2.95	2451 / 3.38	2558 / 3.84	2662 / 4.31			

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.