

RTU1-I.125-16-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000	
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	
600			1222 / 0.19	1474 / 0.31	1690 / 0.44	1881 / 0.58	2055 / 0.72	2214 / 0.88	2362 / 1.04	2510 / 1.22	2643 / 1.40	2765 / 1.57	2885 / 1.76	
840			1280 / 0.25	1519 / 0.39	1728 / 0.54	1913 / 0.70	2084 / 0.87	2240 / 1.04	2386 / 1.23	2530 / 1.43	2658 / 1.62	2791 / 1.84	2907 / 2.04	
1080		1117 / 0.17	1365 / 0.31	1584 / 0.47	1782 / 0.65	1960 / 0.83	2126 / 1.02	2278 / 1.22	2422 / 1.43	2559 / 1.64	2687 / 1.86	2812 / 2.09	2935 / 2.33	
1320	1016 / 0.10	1256 / 0.23	1473 / 0.39	1671 / 0.57	1854 / 0.77	2025 / 0.98	2182 / 1.19	2328 / 1.41	2467 / 1.64	2604 / 1.88	2727 / 2.11	2851 / 2.37	2966 / 2.62	
1560	1201 / 0.16	1407 / 0.32	1598 / 0.50	1777 / 0.69	1945 / 0.91	2102 / 1.13	2251 / 1.37	2393 / 1.61	2528 / 1.86	2658 / 2.12	2781 / 2.39	2900 / 2.66		
1800	1385 / 0.25	1567 / 0.42	1736 / 0.62	1897 / 0.83	2050 / 1.07	2198 / 1.31	2338 / 1.57	2473 / 1.83	2601 / 2.11	2723 / 2.38	2844 / 2.67	2956 / 2.96		
2040	1569 / 0.36	1732 / 0.56	1884 / 0.77	2030 / 1.01	2170 / 1.25	2305 / 1.51	2437 / 1.79	2563 / 2.07	2684 / 2.37	2802 / 2.67	2914 / 2.97			
2280	1754 / 0.50	1900 / 0.72	2038 / 0.95	2171 / 1.21	2301 / 1.47	2426 / 1.75	2547 / 2.04	2667 / 2.35	2780 / 2.66	2893 / 2.98	3000 / 3.30			
2520	1938 / 0.68	2071 / 0.92	2199 / 1.17	2320 / 1.44	2439 / 1.72	2556 / 2.02	2669 / 2.33	2778 / 2.65	2887 / 2.98	2993 / 3.32				
2760	2123 / 0.89	2246 / 1.15	2361 / 1.42	2475 / 1.71	2587 / 2.02	2693 / 2.33	2799 / 2.65	2902 / 2.99						
3000	2308 / 1.15	2419 / 1.43	2530 / 1.72	2634 / 2.03	2737 / 2.35	2838 / 2.68	2938 / 3.03							

Max Sizeable RPM = 3000 RPM. Table shown extended beyond this point for reference only.

Motor 186725/A01—ECM-50-277-16 has an rpm range of 1000 to 2390.

Motor 186725/A01—ECM-60-277-16 has an rpm range of 1000 to 2390.

Motor 186727/A01-ECM-50-480-16 has an rpm range of 1000 to 3000.

Motor 186727/A01-ECM-60-480-16 has an rpm range of 1000 to 3000.

Motor 186728/A01—ECM-50-240-16 has an rpm range of 1000 to 2770.

Motor 186728/A01—ECM-60-240-16 has an rpm range of 1000 to 2770.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 1000 to 2700.