

RTU1-I.125-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
600			1115 / 0.24	1348 / 0.39	1546 / 0.56	1724 / 0.75	1881 / 0.95	2027 / 1.16	2166 / 1.38	2299 / 1.63	2419 / 1.87	2532 / 2.11	2643 / 2.38
840			1151 / 0.30	1379 / 0.48	1576 / 0.67	1750 / 0.88	1905 / 1.10	2054 / 1.34	2188 / 1.59	2314 / 1.84	2435 / 2.11	2553 / 2.39	2658 / 2.66
1080		933 / 0.19	1196 / 0.37	1417 / 0.57	1610 / 0.79	1779 / 1.03	1935 / 1.27	2081 / 1.54	2213 / 1.80	2343 / 2.09	2460 / 2.37	2578 / 2.68	2687 / 2.99
1320		1020 / 0.24	1257 / 0.45	1465 / 0.68	1650 / 0.92	1808 / 1.17	1970 / 1.45	2112 / 1.74	2245 / 2.03	2370 / 2.34	2491 / 2.66	2604 / 2.98	
1560	901 / 0.14	1121 / 0.32	1331 / 0.54	1523 / 0.79	1699 / 1.06	1862 / 1.35	2010 / 1.65	2146 / 1.95	2281 / 2.28	2404 / 2.61	2520 / 2.94	2635 / 3.30	
1800	1039 / 0.21	1230 / 0.41	1417 / 0.65	1594 / 0.93	1760 / 1.22	1913 / 1.53	2057 / 1.85	2192 / 2.19	2320 / 2.53	2442 / 2.89	2557 / 3.25	2671 / 3.63	
2040	1178 / 0.30	1347 / 0.52	1513 / 0.79	1675 / 1.08	1828 / 1.39	1975 / 1.73	2112 / 2.07	2244 / 2.44	2367 / 2.80	2485 / 3.18	2599 / 3.57		
2280	1316 / 0.42	1467 / 0.66	1618 / 0.95	1765 / 1.26	1908 / 1.60	2045 / 1.95	2173 / 2.31	2301 / 2.70	2420 / 3.10	2536 / 3.51	2648 / 3.93		
2520	1455 / 0.57	1592 / 0.83	1728 / 1.13	1863 / 1.46	1994 / 1.82	2123 / 2.20	2246 / 2.59	2366 / 3.00	2480 / 3.41	2593 / 3.85			
2760	1594 / 0.75	1719 / 1.03	1842 / 1.35	1967 / 1.70	2089 / 2.08	2208 / 2.47	2325 / 2.89	2438 / 3.31	2548 / 3.76	2654 / 4.20			
3000	1732 / 0.96	1846 / 1.27	1962 / 1.61	2076 / 1.98	2190 / 2.37	2301 / 2.78	2410 / 3.21	2517 / 3.66	2622 / 4.13				

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.