

RTU1-I.150-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
750			1131 / 0.27	1364 / 0.44	1559 / 0.63	1736 / 0.83	1894 / 1.04	2038 / 1.26	2174 / 1.50	2308 / 1.76	2427 / 2.01	2542 / 2.28	2650 / 2.55
975			1166 / 0.33	1393 / 0.52	1588 / 0.73	1760 / 0.95	1916 / 1.19	2061 / 1.44	2196 / 1.69	2327 / 1.97	2444 / 2.24	2559 / 2.53	2671 / 2.84
1200		961 / 0.20	1213 / 0.40	1430 / 0.61	1619 / 0.84	1788 / 1.09	1945 / 1.35	2087 / 1.62	2222 / 1.90	2348 / 2.19	2469 / 2.50	2581 / 2.80	2691 / 3.12
1425		1046 / 0.26	1271 / 0.47	1475 / 0.71	1659 / 0.96	1825 / 1.23	1976 / 1.52	2108 / 1.79	2251 / 2.12	2375 / 2.43	2496 / 2.76	2610 / 3.10	
1650	931 / 0.14	1141 / 0.33	1343 / 0.56	1531 / 0.81	1705 / 1.09	1864 / 1.38	2012 / 1.69	2151 / 2.01	2282 / 2.34	2405 / 2.67	2523 / 3.02	2636 / 3.38	
1875	1058 / 0.21	1243 / 0.41	1424 / 0.66	1597 / 0.93	1759 / 1.23	1913 / 1.55	2056 / 1.88	2190 / 2.22	2321 / 2.58	2441 / 2.94	2558 / 3.31	2667 / 3.69	
2100	1184 / 0.30	1351 / 0.52	1514 / 0.78	1672 / 1.07	1823 / 1.39	1968 / 1.72	2106 / 2.08	2236 / 2.44	2362 / 2.82	2479 / 3.20	2593 / 3.59		
2325	1311 / 0.40	1462 / 0.64	1610 / 0.92	1755 / 1.23	1896 / 1.57	2032 / 1.92	2163 / 2.29	2288 / 2.68	2407 / 3.07	2524 / 3.49	2636 / 3.91		
2550	1438 / 0.53	1576 / 0.79	1711 / 1.09	1845 / 1.41	1957 / 1.71	2102 / 2.13	2227 / 2.53	2346 / 2.93	2461 / 3.35	2573 / 3.78	2681 / 4.22		
2775	1565 / 0.68	1692 / 0.97	1817 / 1.28	1941 / 1.62	2062 / 1.99	2182 / 2.38	2297 / 2.79	2411 / 3.21	2523 / 3.65	2630 / 4.11			
3000	1692 / 0.86	1808 / 1.16	1926 / 1.50	2041 / 1.86	2154 / 2.24	2266 / 2.65	2375 / 3.07	2479 / 3.50	2588 / 3.98	2691 / 4.44			

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.