

# RTU1-I.200-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		908 / 0.17	1175 / 0.35	1399 / 0.56	1592 / 0.78	1766 / 1.01	1923 / 1.26	2068 / 1.52	2204 / 1.80	2331 / 2.08	2450 / 2.36	2564 / 2.66	2676 / 2.98
1290		970 / 0.21	1214 / 0.40	1429 / 0.63	1619 / 0.87	1789 / 1.13	1946 / 1.40	2087 / 1.67	2224 / 1.97	2350 / 2.26	2467 / 2.56	2585 / 2.90	2693 / 3.22
1480		1042 / 0.25	1263 / 0.46	1465 / 0.70	1648 / 0.96	1814 / 1.23	1968 / 1.52	2111 / 1.83	2242 / 2.13	2368 / 2.45	2487 / 2.78	2601 / 3.12	
1670	906 / 0.12	1119 / 0.30	1320 / 0.53	1509 / 0.78	1683 / 1.06	1845 / 1.35	1995 / 1.66	2136 / 1.98	2266 / 2.31	2393 / 2.65	2511 / 3.00	2622 / 3.35	
1860	1009 / 0.17	1202 / 0.37	1385 / 0.60	1559 / 0.87	1725 / 1.16	1881 / 1.48	2026 / 1.80	2163 / 2.14	2293 / 2.49	2416 / 2.85	2534 / 3.22	2646 / 3.60	
2050	1112 / 0.23	1288 / 0.44	1456 / 0.69	1618 / 0.97	1773 / 1.28	1921 / 1.60	2062 / 1.95	2197 / 2.31	2324 / 2.68	2443 / 3.05	2559 / 3.44	2669 / 3.84	
2240	1215 / 0.30	1378 / 0.53	1532 / 0.79	1683 / 1.08	1829 / 1.40	1968 / 1.74	2103 / 2.10	2233 / 2.48	2358 / 2.87	2475 / 3.27	2590 / 3.68	2699 / 4.10	
2430	1318 / 0.38	1469 / 0.63	1612 / 0.90	1752 / 1.21	1890 / 1.54	2022 / 1.90	2150 / 2.27	2275 / 2.67	2394 / 3.07	2510 / 3.49	2621 / 3.91		
2620	1421 / 0.48	1561 / 0.74	1696 / 1.03	1827 / 1.35	1955 / 1.70	2079 / 2.06	2202 / 2.45	2321 / 2.86	2437 / 3.28	2549 / 3.71	2657 / 4.16		
2810	1524 / 0.59	1656 / 0.87	1782 / 1.17	1905 / 1.51	2024 / 1.86	2143 / 2.25	2259 / 2.65	2373 / 3.07	2485 / 3.51	2592 / 3.95	2697 / 4.41		
3000	1626 / 0.71	1751 / 1.01	1869 / 1.33	1985 / 1.68	2099 / 2.05	2211 / 2.45	2320 / 2.86	2429 / 3.29	2536 / 3.74	2641 / 4.21			

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.