

RTU1-I.75HE-16-FA

| CFM | Static Pressure in Inches W.G. | | | | | | | | | | | | |
|------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | 0.000 | 0.500 | 1.000 | 1.500 | 2.000 | 2.500 | 3.000 | 3.500 | 4.000 | 4.500 | 5.000 | 5.500 | 6.000 |
| | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP |
| 500 | | | 1225 / 0.18 | 1479 / 0.29 | 1695 / 0.41 | 1887 / 0.55 | 2066 / 0.69 | 2222 / 0.84 | 2370 / 0.99 | 2513 / 1.16 | 2646 / 1.32 | 2778 / 1.51 | 2890 / 1.67 |
| 750 | | 1014 / 0.13 | 1298 / 0.24 | 1534 / 0.37 | 1744 / 0.52 | 1928 / 0.68 | 2101 / 0.84 | 2259 / 1.02 | 2404 / 1.20 | 2542 / 1.39 | 2679 / 1.60 | 2809 / 1.81 | 2930 / 2.02 |
| 1000 | | 1156 / 0.19 | 1404 / 0.34 | 1621 / 0.49 | 1815 / 0.66 | 1992 / 0.83 | 2155 / 1.02 | 2304 / 1.21 | 2451 / 1.42 | 2584 / 1.62 | 2717 / 1.85 | 2841 / 2.08 | 2959 / 2.31 |
| 1250 | 1082 / 0.14 | 1320 / 0.28 | 1536 / 0.45 | 1731 / 0.63 | 1911 / 0.82 | 2076 / 1.02 | 2228 / 1.22 | 2376 / 1.44 | 2515 / 1.67 | 2643 / 1.89 | 2772 / 2.14 | 2894 / 2.39 | |
| 1500 | 1299 / 0.24 | 1497 / 0.40 | 1687 / 0.60 | 1863 / 0.80 | 2027 / 1.02 | 2180 / 1.24 | 2326 / 1.47 | 2463 / 1.71 | 2595 / 1.96 | 2722 / 2.21 | 2841 / 2.47 | 2959 / 2.74 | |
| 1750 | 1515 / 0.38 | 1688 / 0.56 | 1854 / 0.78 | 2011 / 1.01 | 2163 / 1.26 | 2306 / 1.51 | 2441 / 1.77 | 2570 / 2.03 | 2692 / 2.29 | 2814 / 2.57 | 2926 / 2.85 | | |
| 2000 | 1732 / 0.57 | 1881 / 0.77 | 2030 / 1.01 | 2174 / 1.26 | 2312 / 1.54 | 2442 / 1.81 | 2571 / 2.10 | 2692 / 2.39 | 2809 / 2.69 | 2920 / 2.98 | | | |
| 2250 | 1948 / 0.81 | 2081 / 1.03 | 2215 / 1.29 | 2344 / 1.56 | 2470 / 1.86 | 2592 / 2.17 | 2711 / 2.48 | 2823 / 2.79 | 2934 / 3.11 | | | | |
| 2500 | 2165 / 1.12 | 2285 / 1.35 | 2406 / 1.63 | 2523 / 1.92 | 2640 / 2.25 | 2753 / 2.58 | 2860 / 2.91 | 2969 / 3.26 | | | | | |
| 2750 | 2381 / 1.49 | 2491 / 1.74 | 2599 / 2.03 | 2709 / 2.35 | 2815 / 2.69 | 2919 / 3.04 | | | | | | | |
| 3000 | 2597 / 1.93 | 2698 / 2.20 | 2799 / 2.51 | 2899 / 2.85 | 2994 / 3.20 | | | | | | | | |

Max Sizeable RPM = 3000 RPM. Table shown extended beyond this point for reference only.

Motor 186725/A01-ECM-50-277-16 has an rpm range of 1000 to 2390.

Motor 186725/A01-ECM-60-277-16 has an rpm range of 1000 to 2390.

Motor 186727/A01-ECM-50-480-16 has an rpm range of 1000 to 3000.

Motor 186727/A01-ECM-60-480-16 has an rpm range of 1000 to 3000.

Motor 186728/A01-ECM-50-240-16 has an rpm range of 1000 to 2770.

Motor 186728/A01-ECM-60-240-16 has an rpm range of 1000 to 2770.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 1000 to 2700.