

RTU2-18-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
500		786 / 0.09	1094 / 0.21	1330 / 0.35	1529 / 0.51	1706 / 0.69	1866 / 0.88	2016 / 1.08	2155 / 1.30
950		852 / 0.14	1138 / 0.31	1369 / 0.50	1568 / 0.70	1743 / 0.92	1900 / 1.15	2047 / 1.40	2184 / 1.65
1400	728 / 0.06	986 / 0.21	1217 / 0.41	1429 / 0.65	1617 / 0.90	1788 / 1.16	1942 / 1.44	2086 / 1.73	2222 / 2.03
1850	962 / 0.14	1165 / 0.33	1348 / 0.55	1525 / 0.82	1693 / 1.10	1850 / 1.41	1998 / 1.73	2139 / 2.07	2270 / 2.42
2300	1195 / 0.26	1364 / 0.49	1516 / 0.75	1663 / 1.04	1807 / 1.35	1946 / 1.69	2081 / 2.06	2209 / 2.43	2335 / 2.82
2750	1429 / 0.45	1573 / 0.71	1705 / 1.01	1831 / 1.32	1955 / 1.67	2075 / 2.04	2193 / 2.42	2307 / 2.82	2423 / 3.25
3200	1662 / 0.70	1790 / 1.01	1905 / 1.34	2015 / 1.69	2123 / 2.06	2230 / 2.46	2334 / 2.87	2439 / 3.31	2540 / 3.76
3650	1896 / 1.04	2009 / 1.39	2112 / 1.75	2212 / 2.14	2309 / 2.55	2403 / 2.97	2497 / 3.41	2589 / 3.87	2680 / 4.35
4100	2130 / 1.48	2232 / 1.87	2326 / 2.27	2413 / 2.68	2503 / 3.13	2588 / 3.58	2673 / 4.06		
4550	2364 / 2.02	2455 / 2.45	2542 / 2.89	2626 / 3.35					
5000	2597 / 2.68	2682 / 3.15							

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 600 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 600 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 600 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 600 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 600 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 600 to 2700.