

RTU2-E.156-18-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
900			1139 / 0.30	1370 / 0.48	1568 / 0.69	1741 / 0.90	1899 / 1.12	2045 / 1.36	2179 / 1.61
1310		969 / 0.21	1211 / 0.40	1425 / 0.63	1615 / 0.87	1785 / 1.12	1941 / 1.39	2086 / 1.68	2220 / 1.97
1720	919 / 0.13	1129 / 0.31	1325 / 0.53	1510 / 0.79	1685 / 1.07	1845 / 1.37	1995 / 1.68	2134 / 2.00	2266 / 2.34
2130	1138 / 0.24	1312 / 0.45	1474 / 0.71	1631 / 0.99	1782 / 1.30	1928 / 1.63	2068 / 1.98	2200 / 2.35	2325 / 2.72
2540	1357 / 0.40	1505 / 0.66	1644 / 0.94	1779 / 1.25	1910 / 1.59	2039 / 1.95	2164 / 2.32	2286 / 2.72	2403 / 3.13
2950	1576 / 0.63	1705 / 0.92	1827 / 1.24	1945 / 1.58	2060 / 1.94	2174 / 2.33	2287 / 2.74	2396 / 3.16	2504 / 3.61
3360	1795 / 0.93	1909 / 1.26	2018 / 1.61	2123 / 1.98	2225 / 2.37	2327 / 2.78	2428 / 3.22	2526 / 3.67	2625 / 4.14
3770	2014 / 1.32	2117 / 1.68	2214 / 2.06	2309 / 2.47	2403 / 2.89	2493 / 3.33	2584 / 3.79	2674 / 4.27	
4180	2233 / 1.80	2326 / 2.20	2415 / 2.62	2501 / 3.05	2587 / 3.51	2671 / 3.98			
4590	2452 / 2.38	2537 / 2.82	2618 / 3.27	2698 / 3.74					
5000	2671 / 3.08								

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.