

RTU2-E.306-18-FA

CFM	Static Pressure in Inches W.G.															
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500	3.750
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100					940 / 0.54	1046 / 0.70	1142 / 0.87	1232 / 1.05	1314 / 1.24	1392 / 1.43	1465 / 1.63	1536 / 1.84	1601 / 2.05	1664 / 2.27	1727 / 2.51	1786 / 2.75
1490					969 / 0.67	1067 / 0.86	1160 / 1.06	1246 / 1.27	1327 / 1.49	1404 / 1.71	1477 / 1.94	1547 / 2.17	1614 / 2.41	1678 / 2.66	1741 / 2.91	1800 / 3.16
1880				924 / 0.61	1019 / 0.81	1108 / 1.03	1193 / 1.26	1273 / 1.49	1350 / 1.74	1423 / 1.99	1494 / 2.25	1561 / 2.52	1628 / 2.79	1691 / 3.06	1752 / 3.35	1811 / 3.63
2270			909 / 0.59	1000 / 0.78	1085 / 1.00	1166 / 1.23	1243 / 1.47	1317 / 1.73	1388 / 2.00	1457 / 2.28	1523 / 2.57	1589 / 2.87	1651 / 3.17	1712 / 3.47	1771 / 3.78	1828 / 4.10
2660		920 / 0.60	1004 / 0.79	1085 / 1.00	1162 / 1.23	1234 / 1.47	1307 / 1.74	1375 / 2.01	1441 / 2.30	1505 / 2.60	1567 / 2.91	1628 / 3.23	1687 / 3.55	1744 / 3.89	1801 / 4.23	1855 / 4.57
3050	958 / 0.64	1031 / 0.84	1105 / 1.05	1178 / 1.28	1248 / 1.52	1315 / 1.78	1381 / 2.06	1444 / 2.35	1505 / 2.65	1565 / 2.97	1623 / 3.30	1680 / 3.63	1735 / 3.98	1789 / 4.33	1843 / 4.70	
3440	1081 / 0.92	1145 / 1.15	1211 / 1.38	1276 / 1.63	1340 / 1.89	1402 / 2.16	1463 / 2.45	1521 / 2.75	1578 / 3.07	1634 / 3.40	1688 / 3.74	1742 / 4.10	1794 / 4.46	1845 / 4.83		
3830	1203 / 1.27	1261 / 1.52	1320 / 1.78	1379 / 2.04	1437 / 2.32	1494 / 2.62	1550 / 2.92	1605 / 3.24	1658 / 3.57	1711 / 3.92	1761 / 4.27	1812 / 4.64				
4220	1326 / 1.69	1378 / 1.97	1431 / 2.26	1485 / 2.54	1538 / 2.84	1591 / 3.15	1643 / 3.47	1693 / 3.81	1744 / 4.16	1793 / 4.51	1840 / 4.88					
4610	1448 / 2.21	1496 / 2.51	1545 / 2.82	1594 / 3.13	1643 / 3.45	1691 / 3.78	1740 / 4.12	1787 / 4.47	1834 / 4.83							
5000	1571 / 2.82	1614 / 3.15	1659 / 3.48	1705 / 3.82	1750 / 4.16	1795 / 4.51	1840 / 4.87									

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 00218ET3H145T-W22 has an rpm range of 900 to 1750.

Motor 00218OT3H145T-S has an rpm range of 900 to 1750.

Motor BMN145-2.0I2-CS-UB1-50 (1200RPM) has an rpm range of 900 to 1200.

Motor BMN145-2.0I2-CS-UB1-60 (1200RPM) has an rpm range of 900 to 1200.

Motor BMN145-2.0I2-ES-UB1-50 (1800RPM) has an rpm range of 900 to 1800.

Motor BMN145-2.0I2-ES-UB1-60 (1800RPM) has an rpm range of 900 to 1800.

Motor DTP0024 has an rpm range of 900 to 1740.

Motor DTP0024-50HZ has an rpm range of 900 to 1415.

Motor DTP0026 has an rpm range of 900 to 1150.

Motor DTP0034 has an rpm range of 900 to 1755.

Motor DTP0034-50HZ has an rpm range of 900 to 1438.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor GP0024 has an rpm range of 900 to 1740.

Motor GP0024-50 has an rpm range of 900 to 1440.

Motor GT0110 has an rpm range of 900 to 1770.

Motor GT0113 has an rpm range of 900 to 1765.