

RTU2-E.306-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		901 / 0.17	1169 / 0.35	1394 / 0.55	1590 / 0.77	1763 / 1.01	1920 / 1.26	2064 / 1.51	2200 / 1.79	2326 / 2.06	2450 / 2.36	2564 / 2.66	2670 / 2.96
1490		1036 / 0.25	1256 / 0.46	1458 / 0.69	1643 / 0.96	1810 / 1.23	1963 / 1.52	2107 / 1.82	2241 / 2.13	2365 / 2.45	2483 / 2.78	2600 / 3.13	
1880	1004 / 0.16	1199 / 0.36	1380 / 0.59	1554 / 0.86	1718 / 1.15	1874 / 1.47	2019 / 1.79	2158 / 2.14	2287 / 2.48	2410 / 2.84	2530 / 3.22	2640 / 3.60	
2270	1213 / 0.29	1377 / 0.52	1530 / 0.78	1679 / 1.07	1823 / 1.39	1964 / 1.74	2098 / 2.10	2225 / 2.47	2350 / 2.86	2467 / 3.25	2582 / 3.67	2693 / 4.09	
2660	1421 / 0.46	1563 / 0.73	1696 / 1.02	1826 / 1.34	1952 / 1.68	2077 / 2.05	2197 / 2.44	2315 / 2.84	2431 / 3.27	2533 / 3.67	2649 / 4.14		
3050	1629 / 0.70	1755 / 1.00	1872 / 1.32	1987 / 1.67	2099 / 2.04	2210 / 2.43	2319 / 2.85	2426 / 3.28	2531 / 3.73	2634 / 4.19			
3440	1838 / 1.00	1949 / 1.33	2056 / 1.69	2158 / 2.07	2259 / 2.46	2359 / 2.89	2457 / 3.32	2554 / 3.78	2650 / 4.26				
3830	2046 / 1.38	2147 / 1.75	2244 / 2.14	2337 / 2.55	2429 / 2.97	2520 / 3.42	2609 / 3.89	2697 / 4.37					
4220	2253 / 1.85	2347 / 2.26	2435 / 2.68	2521 / 3.12	2605 / 3.57	2688 / 4.05							
4610	2463 / 2.41	2547 / 2.85	2628 / 3.30										
5000	2671 / 3.08												

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.