

**RTU2-E.452-18-FA**

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500					970 / 0.67	1068 / 0.87	1160 / 1.07	1246 / 1.28	1327 / 1.50	1404 / 1.72	1478 / 1.95	1548 / 2.19	1615 / 2.42	1678 / 2.67	1740 / 2.92
1850				919 / 0.60	1014 / 0.80	1104 / 1.02	1190 / 1.24	1271 / 1.48	1347 / 1.72	1421 / 1.97	1492 / 2.23	1560 / 2.49	1626 / 2.76	1689 / 3.03	1750 / 3.31
2200				985 / 0.75	1072 / 0.96	1154 / 1.19	1233 / 1.43	1308 / 1.69	1380 / 1.95	1450 / 2.23	1517 / 2.51	1583 / 2.80	1645 / 3.10	1707 / 3.40	1766 / 3.70
2550			976 / 0.73	1060 / 0.93	1139 / 1.16	1215 / 1.40	1288 / 1.66	1358 / 1.93	1425 / 2.21	1490 / 2.51	1554 / 2.81	1615 / 3.12	1675 / 3.44	1734 / 3.77	1791 / 4.10
2900	911 / 0.55	988 / 0.74	1066 / 0.95	1141 / 1.17	1214 / 1.40	1284 / 1.66	1351 / 1.93	1417 / 2.21	1480 / 2.51	1541 / 2.82	1600 / 3.14	1658 / 3.47	1715 / 3.81	1770 / 4.16	1825 / 4.51
3250	1021 / 0.77	1090 / 0.99	1159 / 1.21	1227 / 1.45	1294 / 1.70	1359 / 1.97	1422 / 2.25	1483 / 2.55	1542 / 2.86	1599 / 3.18	1656 / 3.52	1711 / 3.86	1764 / 4.22	1817 / 4.58	1868 / 4.95
3600	1131 / 1.05	1192 / 1.29	1255 / 1.53	1318 / 1.79	1379 / 2.06	1439 / 2.34	1498 / 2.63	1554 / 2.94	1610 / 3.27	1664 / 3.60	1718 / 3.95	1769 / 4.31	1820 / 4.68		
3950	1241 / 1.39	1297 / 1.65	1354 / 1.92	1411 / 2.19	1468 / 2.47	1523 / 2.77	1578 / 3.08	1632 / 3.40	1684 / 3.74	1735 / 4.09	1785 / 4.45	1835 / 4.82			
4300	1351 / 1.79	1402 / 2.08	1455 / 2.36	1507 / 2.66	1560 / 2.96	1611 / 3.27	1662 / 3.60	1712 / 3.94	1762 / 4.29	1810 / 4.64					
4650	1461 / 2.27	1508 / 2.57	1556 / 2.88	1605 / 3.20	1654 / 3.52	1702 / 3.85	1749 / 4.19	1797 / 4.55	1843 / 4.91						
5000	1571 / 2.82	1614 / 3.15	1659 / 3.48	1705 / 3.82	1750 / 4.16	1795 / 4.51	1840 / 4.87								

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 00218ET3H145T-W22 has an rpm range of 900 to 1750.

Motor 00218OT3H145T-S has an rpm range of 900 to 1750.

Motor BMN145-2.0I2-CS-UB1-50 (1200RPM) has an rpm range of 900 to 1200.

Motor BMN145-2.0I2-CS-UB1-60 (1200RPM) has an rpm range of 900 to 1200.

Motor BMN145-2.0I2-ES-UB1-50 (1800RPM) has an rpm range of 900 to 1800.

Motor BMN145-2.0I2-ES-UB1-60 (1800RPM) has an rpm range of 900 to 1800.

Motor DTP0024 has an rpm range of 900 to 1740.

Motor DTP0024-50HZ has an rpm range of 900 to 1415.

Motor DTP0026 has an rpm range of 900 to 1150.

Motor DTP0034 has an rpm range of 900 to 1755.

Motor DTP0034-50HZ has an rpm range of 900 to 1438.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor GP0024 has an rpm range of 900 to 1740.

Motor GP0024-50 has an rpm range of 900 to 1440.

Motor GT0110 has an rpm range of 900 to 1770.

Motor GT0113 has an rpm range of 900 to 1765.