

RTU2-E.452-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500		1040 / 0.25	1258 / 0.46	1461 / 0.70	1643 / 0.96	1812 / 1.24	1963 / 1.52	2107 / 1.83	2242 / 2.14	2366 / 2.46	2488 / 2.80	2600 / 3.13
1850	988 / 0.16	1186 / 0.35	1369 / 0.58	1546 / 0.85	1711 / 1.14	1869 / 1.45	2015 / 1.77	2154 / 2.11	2284 / 2.46	2409 / 2.82	2524 / 3.18	2639 / 3.57
2200	1175 / 0.26	1344 / 0.48	1502 / 0.74	1654 / 1.03	1802 / 1.34	1945 / 1.68	2081 / 2.04	2213 / 2.41	2338 / 2.79	2458 / 3.19	2573 / 3.59	2683 / 4.00
2550	1362 / 0.41	1510 / 0.66	1648 / 0.95	1782 / 1.26	1913 / 1.59	2042 / 1.95	2167 / 2.33	2289 / 2.74	2406 / 3.15	2520 / 3.57	2629 / 4.01	
2900	1549 / 0.60	1680 / 0.88	1803 / 1.19	1923 / 1.53	2041 / 1.89	2156 / 2.27	2269 / 2.68	2381 / 3.10	2491 / 3.55	2596 / 3.99		
3250	1736 / 0.85	1854 / 1.16	1966 / 1.50	2074 / 1.86	2180 / 2.25	2286 / 2.66	2388 / 3.08	2490 / 3.53	2590 / 3.99	2688 / 4.46		
3600	1923 / 1.15	2030 / 1.50	2133 / 1.87	2230 / 2.25	2329 / 2.67	2424 / 3.10	2517 / 3.54	2612 / 4.02				
3950	2110 / 1.52	2208 / 1.90	2302 / 2.29	2392 / 2.71	2483 / 3.15	2570 / 3.60	2658 / 4.08					
4300	2296 / 1.96	2388 / 2.37	2474 / 2.80	2560 / 3.25	2641 / 3.70							
4650	2484 / 2.48	2568 / 2.92	2650 / 3.38									
5000	2671 / 3.08											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.