

# RTU2-E.456-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500		1040 / 0.25	1258 / 0.46	1461 / 0.70	1643 / 0.96	1812 / 1.24	1963 / 1.52	2107 / 1.83	2242 / 2.14	2366 / 2.46	2488 / 2.80	2600 / 3.13
1900	1015 / 0.17	1208 / 0.37	1387 / 0.60	1560 / 0.87	1723 / 1.16	1877 / 1.48	2023 / 1.81	2162 / 2.15	2292 / 2.51	2414 / 2.87	2533 / 3.25	2643 / 3.62
2300	1229 / 0.30	1391 / 0.53	1542 / 0.79	1689 / 1.09	1833 / 1.41	1971 / 1.76	2104 / 2.12	2233 / 2.50	2357 / 2.89	2473 / 3.29	2587 / 3.71	2696 / 4.13
2700	1442 / 0.49	1583 / 0.75	1714 / 1.05	1842 / 1.37	1966 / 1.72	2090 / 2.09	2209 / 2.48	2326 / 2.88	2441 / 3.32	2552 / 3.75	2657 / 4.20	
3100	1656 / 0.73	1780 / 1.04	1896 / 1.36	2009 / 1.71	2119 / 2.09	2229 / 2.49	2336 / 2.90	2441 / 3.33	2545 / 3.79	2647 / 4.26		
3500	1870 / 1.06	1980 / 1.39	2085 / 1.75	2186 / 2.14	2285 / 2.54	2383 / 2.96	2481 / 3.41	2575 / 3.87	2670 / 4.34			
3900	2083 / 1.46	2182 / 1.83	2278 / 2.23	2369 / 2.64	2461 / 3.08	2549 / 3.53	2637 / 4.00					
4300	2296 / 1.96	2388 / 2.37	2474 / 2.80	2560 / 3.25	2641 / 3.70							
4700	2511 / 2.56	2594 / 3.00	2673 / 3.47									

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.