

## RTU2-E.602-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900	1015 / 0.17	1208 / 0.37	1387 / 0.60	1560 / 0.87	1723 / 1.16	1877 / 1.48	2023 / 1.81	2162 / 2.15	2292 / 2.51	2414 / 2.87	2533 / 3.25	2643 / 3.62
2190	1170 / 0.26	1339 / 0.48	1498 / 0.74	1652 / 1.03	1800 / 1.34	1943 / 1.68	2080 / 2.03	2210 / 2.40	2337 / 2.78	2455 / 3.17	2570 / 3.58	2681 / 3.99
2480	1325 / 0.38	1476 / 0.62	1618 / 0.90	1755 / 1.21	1890 / 1.54	2021 / 1.90	2149 / 2.27	2271 / 2.66	2392 / 3.07	2505 / 3.49	2616 / 3.92	
2770	1480 / 0.52	1616 / 0.80	1745 / 1.10	1870 / 1.42	1991 / 1.77	2113 / 2.15	2230 / 2.55	2345 / 2.96	2458 / 3.39	2567 / 3.84	2674 / 4.30	
3060	1635 / 0.71	1760 / 1.00	1877 / 1.33	1991 / 1.67	2103 / 2.05	2214 / 2.44	2322 / 2.85	2429 / 3.29	2535 / 3.74	2638 / 4.21		
3350	1790 / 0.93	1904 / 1.25	2013 / 1.60	2118 / 1.97	2221 / 2.36	2323 / 2.77	2424 / 3.21	2524 / 3.66	2621 / 4.13			
3640	1944 / 1.19	2051 / 1.54	2151 / 1.91	2250 / 2.30	2345 / 2.72	2440 / 3.15	2533 / 3.60	2626 / 4.07				
3930	2099 / 1.50	2198 / 1.87	2293 / 2.27	2383 / 2.68	2473 / 3.12	2562 / 3.57	2650 / 4.05					
4220	2253 / 1.85	2347 / 2.26	2435 / 2.68	2521 / 3.12	2605 / 3.57	2688 / 4.05						
4510	2409 / 2.26	2496 / 2.69	2579 / 3.13	2661 / 3.60								
4800	2564 / 2.73	2646 / 3.18										

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.