

RTU2-E.604-18-FA

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900			941 / 0.30	1078 / 0.45	1199 / 0.60	1308 / 0.77	1407 / 0.94	1500 / 1.12	1586 / 1.31	1667 / 1.50	1743 / 1.70	1816 / 1.91	1887 / 2.12	1953 / 2.33	2019 / 2.55
2210			1005 / 0.36	1130 / 0.52	1246 / 0.69	1353 / 0.87	1451 / 1.06	1542 / 1.26	1627 / 1.46	1708 / 1.67	1784 / 1.88	1857 / 2.10	1927 / 2.33	1993 / 2.55	2058 / 2.79
2520		961 / 0.30	1076 / 0.44	1190 / 0.61	1300 / 0.79	1402 / 0.99	1497 / 1.19	1587 / 1.40	1671 / 1.62	1751 / 1.85	1826 / 2.07	1899 / 2.31	1967 / 2.54	2034 / 2.79	2098 / 3.04
2830	961 / 0.26	1054 / 0.38	1155 / 0.53	1258 / 0.71	1359 / 0.91	1456 / 1.12	1547 / 1.33	1634 / 1.56	1717 / 1.79	1796 / 2.03	1870 / 2.27	1942 / 2.53	2010 / 2.78	2076 / 3.04	2141 / 3.30
3140	1066 / 0.35	1149 / 0.48	1239 / 0.65	1331 / 0.83	1423 / 1.04	1514 / 1.26	1601 / 1.49	1685 / 1.73	1766 / 1.98	1843 / 2.23	1916 / 2.49	1986 / 2.75	2055 / 3.02	2120 / 3.30	2184 / 3.58
3450	1171 / 0.46	1246 / 0.61	1327 / 0.78	1410 / 0.97	1495 / 1.19	1578 / 1.42	1661 / 1.66	1741 / 1.91	1818 / 2.17	1892 / 2.44	1965 / 2.71	2033 / 2.99	2100 / 3.27	2166 / 3.57	2227 / 3.86
3760	1277 / 0.60	1345 / 0.76	1418 / 0.94	1493 / 1.14	1571 / 1.36	1648 / 1.60	1725 / 1.85	1801 / 2.11	1874 / 2.39	1946 / 2.67	2016 / 2.96	2083 / 3.25	2149 / 3.55	2212 / 3.85	2273 / 4.16
4070	1382 / 0.76	1445 / 0.93	1511 / 1.12	1581 / 1.33	1651 / 1.56	1722 / 1.80	1794 / 2.06	1865 / 2.34	1934 / 2.62	2003 / 2.91	2070 / 3.21	2135 / 3.52	2200 / 3.84	2261 / 4.15	2322 / 4.48
4380	1487 / 0.95	1545 / 1.13	1607 / 1.33	1670 / 1.54	1735 / 1.78	1801 / 2.04	1868 / 2.31	1934 / 2.59	2000 / 2.88	2065 / 3.18	2129 / 3.50	2192 / 3.82	2254 / 4.15	2314 / 4.48	2373 / 4.81
4690	1593 / 1.16	1646 / 1.35	1703 / 1.56	1762 / 1.79	1822 / 2.04	1883 / 2.30	1945 / 2.58	2008 / 2.87	2070 / 3.17	2131 / 3.48	2193 / 3.81	2253 / 4.14	2311 / 4.47	2366 / 4.80	
5000	1698 / 1.41	1748 / 1.61	1801 / 1.83	1855 / 2.07	1911 / 2.32	1969 / 2.59	2026 / 2.88	2084 / 3.17	2142 / 3.48	2201 / 3.81	2258 / 4.14	2311 / 4.45	2373 / 4.83		

Max Sizeable RPM = 2600 RPM. Table shown extended beyond this point for reference only.

Motor 00218ET3H145T-W22 has an rpm range of 900 to 1750.

Motor 00218OT3H145T-S has an rpm range of 900 to 1750.

Motor 00536OT3H182T-S has an rpm range of 900 to 2600.

Motor BMN145-2.0I2-CS-UB1-50 (1200RPM) has an rpm range of 900 to 1200.

Motor BMN145-2.0I2-CS-UB1-60 (1200RPM) has an rpm range of 900 to 1200.

Motor BMN145-2.0I2-ES-UB1-50 (1800RPM) has an rpm range of 900 to 1800.

Motor BMN145-2.0I2-ES-UB1-60 (1800RPM) has an rpm range of 900 to 1800.

Motor DTP0024 has an rpm range of 900 to 1740.

Motor DTP0024-50HZ has an rpm range of 900 to 1415.

Motor DTP0026 has an rpm range of 900 to 1150.

Motor DTP0034 has an rpm range of 900 to 1755.

Motor DTP0034-50HZ has an rpm range of 900 to 1438.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor GP0024 has an rpm range of 900 to 1740.

Motor GP0024-50 has an rpm range of 900 to 1440.

Motor GT0110 has an rpm range of 900 to 1770.

Motor GT0113 has an rpm range of 900 to 1765.