

# RTU2-E.604-18-FA

CFM	Static Pressure in Inches W.G.										
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900	1015 / 0.17	1208 / 0.37	1387 / 0.60	1560 / 0.87	1723 / 1.16	1877 / 1.48	2023 / 1.81	2162 / 2.15	2292 / 2.51	2414 / 2.87	2533 / 3.25
2210	1181 / 0.27	1348 / 0.49	1504 / 0.75	1658 / 1.04	1806 / 1.35	1947 / 1.69	2085 / 2.05	2214 / 2.42	2339 / 2.80	2458 / 3.19	2573 / 3.60
2520	1346 / 0.39	1496 / 0.64	1635 / 0.93	1771 / 1.24	1903 / 1.57	2032 / 1.93	2159 / 2.31	2281 / 2.70	2400 / 3.12	2515 / 3.54	2625 / 3.98
2830	1512 / 0.56	1646 / 0.84	1772 / 1.14	1894 / 1.47	2014 / 1.83	2133 / 2.21	2248 / 2.61	2362 / 3.03	2472 / 3.46	2580 / 3.91	2685 / 4.37
3140	1677 / 0.76	1799 / 1.07	1915 / 1.40	2026 / 1.75	2135 / 2.13	2243 / 2.53	2350 / 2.95	2455 / 3.39	2557 / 3.84	2659 / 4.31	
3450	1843 / 1.01	1955 / 1.35	2061 / 1.70	2163 / 2.08	2264 / 2.48	2363 / 2.90	2461 / 3.34	2557 / 3.79	2654 / 4.27		
3760	2009 / 1.31	2111 / 1.67	2209 / 2.05	2305 / 2.46	2398 / 2.88	2490 / 3.32	2581 / 3.78	2670 / 4.26			
4070	2174 / 1.66	2269 / 2.05	2361 / 2.46	2450 / 2.89	2537 / 3.33	2622 / 3.80					
4380	2338 / 2.07	2428 / 2.49	2514 / 2.92	2598 / 3.38	2679 / 3.85						
4690	2505 / 2.54	2588 / 2.99	2669 / 3.45								
5000	2671 / 3.08										

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.