

RTU2-I.100-18-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
750			1143 / 0.28	1374 / 0.45	1569 / 0.63	1744 / 0.84	1904 / 1.07	2049 / 1.30	2187 / 1.56
1120		967 / 0.21	1223 / 0.40	1440 / 0.60	1628 / 0.82	1798 / 1.05	1951 / 1.30	2093 / 1.56	2227 / 1.84
1490		1119 / 0.31	1335 / 0.55	1530 / 0.80	1707 / 1.07	1867 / 1.33	2016 / 1.61	2156 / 1.91	2285 / 2.21
1860	1110 / 0.26	1295 / 0.45	1476 / 0.72	1647 / 1.03	1806 / 1.34	1956 / 1.66	2097 / 1.99	2230 / 2.32	2357 / 2.67
2230	1331 / 0.46	1486 / 0.65	1639 / 0.94	1788 / 1.29	1931 / 1.66	2069 / 2.04	2199 / 2.42	2323 / 2.80	2442 / 3.19
2600	1552 / 0.72	1684 / 0.92	1817 / 1.23	1948 / 1.61	2075 / 2.02	2198 / 2.44	2319 / 2.88	2434 / 3.32	2547 / 3.76
2970	1773 / 1.08	1888 / 1.28	2005 / 1.61	2120 / 2.00	2235 / 2.44	2346 / 2.90	2455 / 3.38	2560 / 3.87	2666 / 4.38
3340	1994 / 1.53	2097 / 1.75	2200 / 2.08	2303 / 2.48	2405 / 2.94	2506 / 3.43	2605 / 3.95		
3710	2215 / 2.10	2307 / 2.33	2400 / 2.66	2493 / 3.08	2585 / 3.55	2677 / 4.06			
4080	2436 / 2.79	2520 / 3.04	2604 / 3.37	2688 / 3.79					
4450	2657 / 3.62								

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.