

RTU2-I.150-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
750			1131 / 0.27	1364 / 0.44	1559 / 0.63	1736 / 0.83	1894 / 1.04	2038 / 1.26	2174 / 1.50	2308 / 1.76	2427 / 2.01	2542 / 2.28	2650 / 2.55
1150		943 / 0.19	1202 / 0.38	1420 / 0.59	1611 / 0.82	1783 / 1.06	1939 / 1.32	2083 / 1.58	2216 / 1.85	2342 / 2.14	2463 / 2.44	2578 / 2.75	2687 / 3.06
1550		1098 / 0.30	1309 / 0.52	1505 / 0.76	1683 / 1.03	1845 / 1.32	1997 / 1.62	2138 / 1.92	2269 / 2.24	2392 / 2.57	2512 / 2.91	2623 / 3.25	
1950	1099 / 0.24	1280 / 0.45	1453 / 0.70	1621 / 0.98	1779 / 1.28	1931 / 1.61	2072 / 1.94	2206 / 2.29	2333 / 2.65	2453 / 3.02	2569 / 3.41	2679 / 3.79	
2350	1325 / 0.41	1475 / 0.66	1622 / 0.94	1764 / 1.25	1904 / 1.59	2040 / 1.94	2170 / 2.32	2295 / 2.71	2413 / 3.10	2530 / 3.52	2640 / 3.94		
2750	1550 / 0.66	1679 / 0.94	1806 / 1.26	1930 / 1.60	2052 / 1.96	2172 / 2.35	2290 / 2.76	2404 / 3.18	2514 / 3.61	2622 / 4.06			
3150	1776 / 1.00	1888 / 1.31	2000 / 1.66	2108 / 2.03	2217 / 2.43	2325 / 2.85	2429 / 3.28	2534 / 3.74	2636 / 4.21				
3550	2001 / 1.43	2102 / 1.78	2201 / 2.16	2298 / 2.56	2395 / 2.99	2491 / 3.44	2586 / 3.90	2679 / 4.38					
3950	2227 / 1.97	2317 / 2.36	2406 / 2.77	2494 / 3.21	2582 / 3.67	2669 / 4.14							
4350	2452 / 2.63	2533 / 3.05	2616 / 3.51	2695 / 3.97									
4750	2678 / 3.42												

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.