

RTU2-I.150HE-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
750			1135 / 0.28	1366 / 0.44	1562 / 0.63	1740 / 0.83	1899 / 1.05	2044 / 1.27	2180 / 1.51	2308 / 1.76	2427 / 2.01	2542 / 2.28	2660 / 2.58
1125		948 / 0.20	1206 / 0.38	1424 / 0.59	1616 / 0.82	1786 / 1.05	1940 / 1.30	2083 / 1.57	2219 / 1.84	2344 / 2.12	2467 / 2.43	2580 / 2.73	2691 / 3.05
1500		1093 / 0.29	1310 / 0.51	1508 / 0.76	1685 / 1.02	1850 / 1.31	2000 / 1.60	2140 / 1.90	2269 / 2.21	2396 / 2.54	2513 / 2.87	2627 / 3.22	
1875	1081 / 0.23	1265 / 0.44	1445 / 0.69	1616 / 0.97	1779 / 1.27	1929 / 1.58	2072 / 1.92	2206 / 2.26	2335 / 2.62	2454 / 2.98	2568 / 3.34	2682 / 3.74	
2250	1296 / 0.40	1451 / 0.64	1603 / 0.92	1751 / 1.23	1896 / 1.56	2033 / 1.91	2166 / 2.28	2291 / 2.66	2412 / 3.05	2528 / 3.46	2641 / 3.88		
2625	1512 / 0.64	1645 / 0.91	1776 / 1.22	1906 / 1.56	2033 / 1.92	2157 / 2.31	2277 / 2.70	2391 / 3.11	2507 / 3.55	2617 / 3.99			
3000	1728 / 0.95	1844 / 1.26	1960 / 1.60	2075 / 1.97	2187 / 2.36	2299 / 2.78	2408 / 3.21	2515 / 3.65	2620 / 4.12				
3375	1944 / 1.36	2048 / 1.70	2150 / 2.07	2253 / 2.47	2354 / 2.89	2455 / 3.33	2553 / 3.79	2651 / 4.27					
3750	2160 / 1.86	2252 / 2.24	2345 / 2.64	2438 / 3.07	2530 / 3.53	2621 / 3.99							
4125	2376 / 2.47	2461 / 2.89	2545 / 3.33	2629 / 3.79									
4500	2592 / 3.21	2669 / 3.66											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.