

## RTU2-I.200-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		908 / 0.17	1175 / 0.35	1399 / 0.56	1592 / 0.78	1766 / 1.01	1923 / 1.26	2068 / 1.52	2204 / 1.80	2331 / 2.08	2450 / 2.36	2564 / 2.66
1480		1042 / 0.25	1263 / 0.46	1465 / 0.70	1648 / 0.96	1814 / 1.23	1968 / 1.52	2111 / 1.83	2242 / 2.13	2368 / 2.45	2487 / 2.78	2601 / 3.12
1860	1009 / 0.17	1202 / 0.37	1385 / 0.60	1559 / 0.87	1725 / 1.16	1881 / 1.48	2026 / 1.80	2163 / 2.14	2293 / 2.49	2416 / 2.85	2534 / 3.22	2646 / 3.60
2240	1215 / 0.30	1378 / 0.53	1532 / 0.79	1683 / 1.08	1829 / 1.40	1968 / 1.74	2103 / 2.10	2233 / 2.48	2358 / 2.87	2475 / 3.27	2590 / 3.68	2699 / 4.10
2620	1421 / 0.48	1561 / 0.74	1696 / 1.03	1827 / 1.35	1955 / 1.70	2079 / 2.06	2202 / 2.45	2321 / 2.86	2437 / 3.28	2549 / 3.71	2657 / 4.16	
3000	1626 / 0.71	1751 / 1.01	1869 / 1.33	1985 / 1.68	2099 / 2.05	2211 / 2.45	2320 / 2.86	2429 / 3.29	2536 / 3.74	2641 / 4.21		
3380	1833 / 1.02	1944 / 1.35	2050 / 1.71	2154 / 2.08	2256 / 2.48	2357 / 2.90	2456 / 3.34	2555 / 3.80	2653 / 4.28			
3760	2039 / 1.41	2139 / 1.77	2235 / 2.16	2330 / 2.57	2423 / 2.99	2515 / 3.44	2606 / 3.91	2695 / 4.39				
4140	2245 / 1.88	2336 / 2.28	2425 / 2.70	2511 / 3.14	2596 / 3.59	2680 / 4.07						
4520	2451 / 2.45	2535 / 2.88	2616 / 3.33	2697 / 3.81								
4900	2657 / 3.12											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.