

RTU2-I.200HE-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		919 / 0.18	1184 / 0.36	1407 / 0.57	1599 / 0.79	1771 / 1.02	1926 / 1.27	2072 / 1.53	2209 / 1.81	2335 / 2.09	2455 / 2.38	2570 / 2.68
1470		1053 / 0.26	1274 / 0.47	1476 / 0.71	1657 / 0.97	1824 / 1.25	1976 / 1.54	2118 / 1.84	2251 / 2.15	2375 / 2.46	2496 / 2.80	2606 / 3.12
1840	1021 / 0.18	1213 / 0.38	1396 / 0.62	1571 / 0.89	1737 / 1.18	1893 / 1.50	2038 / 1.82	2175 / 2.16	2303 / 2.51	2427 / 2.87	2541 / 3.23	2647 / 3.59
2210	1226 / 0.32	1387 / 0.55	1542 / 0.81	1695 / 1.11	1840 / 1.43	1982 / 1.78	2117 / 2.14	2246 / 2.51	2369 / 2.89	2489 / 3.30	2600 / 3.70	
2580	1431 / 0.51	1570 / 0.77	1705 / 1.06	1838 / 1.39	1966 / 1.74	2092 / 2.10	2216 / 2.50	2335 / 2.90	2450 / 3.32	2562 / 3.75	2671 / 4.20	
2950	1636 / 0.76	1758 / 1.05	1878 / 1.38	1995 / 1.73	2109 / 2.10	2223 / 2.50	2334 / 2.92	2444 / 3.35	2550 / 3.80	2655 / 4.27		
3320	1841 / 1.08	1951 / 1.41	2057 / 1.77	2161 / 2.14	2265 / 2.55	2366 / 2.97	2468 / 3.41	2568 / 3.87	2667 / 4.35			
3690	2047 / 1.48	2145 / 1.85	2240 / 2.23	2335 / 2.64	2429 / 3.07	2522 / 3.52	2615 / 3.99					
4060	2252 / 1.98	2341 / 2.37	2430 / 2.79	2515 / 3.23	2601 / 3.69	2687 / 4.17						
4430	2457 / 2.57	2539 / 3.00	2620 / 3.45	2700 / 3.92								
4800	2662 / 3.27											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.