

RTU2-I.250-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		905 / 0.17	1173 / 0.35	1398 / 0.56	1592 / 0.78	1763 / 1.01	1920 / 1.26	2068 / 1.52	2200 / 1.79	2331 / 2.08	2450 / 2.36	2564 / 2.66
1575		1075 / 0.27	1286 / 0.49	1482 / 0.74	1661 / 1.00	1827 / 1.29	1979 / 1.59	2120 / 1.90	2253 / 2.22	2379 / 2.55	2496 / 2.88	2612 / 3.24
2050	1108 / 0.22	1283 / 0.43	1451 / 0.68	1613 / 0.96	1769 / 1.27	1916 / 1.59	2058 / 1.94	2193 / 2.30	2319 / 2.66	2440 / 3.04	2556 / 3.43	2666 / 3.82
2525	1364 / 0.42	1508 / 0.67	1646 / 0.95	1782 / 1.26	1914 / 1.60	2045 / 1.96	2169 / 2.34	2291 / 2.74	2409 / 3.15	2522 / 3.57	2633 / 4.01	
3000	1621 / 0.70	1743 / 0.99	1861 / 1.31	1976 / 1.65	2091 / 2.02	2203 / 2.42	2313 / 2.83	2421 / 3.26	2527 / 3.71	2625 / 4.14		
3475	1877 / 1.09	1983 / 1.42	2086 / 1.78	2187 / 2.16	2288 / 2.56	2385 / 2.98	2484 / 3.43	2580 / 3.89	2675 / 4.38			
3950	2134 / 1.61	2228 / 1.98	2319 / 2.37	2409 / 2.79	2497 / 3.22	2585 / 3.68	2673 / 4.16					
4425	2389 / 2.25	2475 / 2.67	2556 / 3.10	2635 / 3.55								
4900	2647 / 3.07											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.