

RTU2-I.250HE-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		905 / 0.17	1171 / 0.35	1396 / 0.55	1592 / 0.78	1763 / 1.01	1920 / 1.26	2068 / 1.52	2200 / 1.79	2331 / 2.08	2450 / 2.36	2564 / 2.66
1840	994 / 0.16	1188 / 0.35	1372 / 0.59	1549 / 0.85	1715 / 1.14	1872 / 1.45	2018 / 1.77	2157 / 2.11	2286 / 2.46	2412 / 2.82	2527 / 3.18	2640 / 3.56
2580	1394 / 0.45	1534 / 0.70	1670 / 0.98	1803 / 1.30	1928 / 1.63	2061 / 2.01	2185 / 2.39	2304 / 2.79	2420 / 3.21	2534 / 3.64	2643 / 4.08	
3320	1794 / 0.95	1904 / 1.27	2011 / 1.61	2116 / 1.98	2219 / 2.37	2323 / 2.78	2423 / 3.21	2525 / 3.67	2622 / 4.14			
4060	2192 / 1.74	2283 / 2.12	2370 / 2.51	2461 / 2.95	2545 / 3.39	2631 / 3.85						
4800	2593 / 2.88	2670 / 3.32										

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.