

RTU2-I.300-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100			1168 / 0.35	1392 / 0.55	1587 / 0.77	1760 / 1.01	1916 / 1.25	2064 / 1.52	2200 / 1.79	2326 / 2.06	2444 / 2.35	2564 / 2.66
1480		1028 / 0.24	1251 / 0.45	1455 / 0.69	1639 / 0.95	1805 / 1.22	1958 / 1.50	2102 / 1.81	2236 / 2.11	2360 / 2.43	2479 / 2.76	2596 / 3.10
1860	1005 / 0.17	1185 / 0.35	1369 / 0.58	1545 / 0.85	1713 / 1.14	1867 / 1.45	2015 / 1.78	2153 / 2.11	2282 / 2.46	2406 / 2.82	2524 / 3.19	2635 / 3.56
2240	1210 / 0.29	1358 / 0.50	1510 / 0.75	1663 / 1.04	1811 / 1.36	1953 / 1.71	2088 / 2.06	2218 / 2.44	2343 / 2.82	2462 / 3.22	2575 / 3.62	2683 / 4.03
2620	1415 / 0.47	1541 / 0.70	1671 / 0.97	1802 / 1.29	1931 / 1.63	2058 / 2.00	2183 / 2.39	2302 / 2.79	2419 / 3.21	2531 / 3.64	2641 / 4.09	
3000	1620 / 0.70	1730 / 0.96	1843 / 1.26	1957 / 1.59	2070 / 1.96	2183 / 2.35	2295 / 2.76	2392 / 3.14	2513 / 3.64	2618 / 4.11		
3380	1825 / 1.00	1923 / 1.29	2022 / 1.61	2123 / 1.97	2224 / 2.35	2325 / 2.77	2426 / 3.21	2513 / 3.60	2624 / 4.14			
3760	2030 / 1.38	2117 / 1.69	2207 / 2.04	2297 / 2.42	2387 / 2.83	2479 / 3.26	2570 / 3.72	2661 / 4.20				
4140	2235 / 1.85	2314 / 2.18	2394 / 2.55	2476 / 2.96	2559 / 3.39	2640 / 3.84						
4520	2441 / 2.40	2513 / 2.77	2586 / 3.16	2660 / 3.59								
4900	2646 / 3.06											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.