

RTU2-I.300HE-18-FA

CFM	Static Pressure in Inches W.G.											
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100		902 / 0.17	1170 / 0.35	1394 / 0.55	1590 / 0.78	1763 / 1.01	1920 / 1.26	2064 / 1.51	2200 / 1.79	2326 / 2.06	2450 / 2.36	2564 / 2.66
1470		1028 / 0.24	1252 / 0.45	1455 / 0.69	1639 / 0.94	1806 / 1.22	1960 / 1.50	2103 / 1.80	2237 / 2.11	2363 / 2.43	2483 / 2.76	2597 / 3.10
1840	994 / 0.16	1182 / 0.35	1365 / 0.58	1544 / 0.84	1712 / 1.14	1868 / 1.44	2015 / 1.77	2152 / 2.10	2283 / 2.45	2405 / 2.80	2524 / 3.17	2636 / 3.55
2210	1194 / 0.28	1350 / 0.49	1505 / 0.75	1659 / 1.04	1807 / 1.36	1951 / 1.70	2087 / 2.05	2217 / 2.42	2341 / 2.81	2461 / 3.20	2576 / 3.61	2685 / 4.02
2580	1393 / 0.45	1528 / 0.69	1661 / 0.96	1794 / 1.28	1925 / 1.62	2053 / 1.98	2177 / 2.37	2299 / 2.78	2416 / 3.19	2529 / 3.62	2638 / 4.06	
2950	1593 / 0.67	1710 / 0.93	1828 / 1.24	1945 / 1.58	2060 / 1.94	2176 / 2.33	2289 / 2.74	2398 / 3.17	2506 / 3.61	2613 / 4.08		
3320	1793 / 0.95	1897 / 1.25	2001 / 1.58	2105 / 1.94	2209 / 2.32	2312 / 2.74	2415 / 3.17	2515 / 3.63	2614 / 4.10			
3690	1992 / 1.31	2087 / 1.63	2181 / 1.99	2275 / 2.38	2368 / 2.79	2462 / 3.22	2554 / 3.68	2645 / 4.15				
4060	2192 / 1.74	2278 / 2.10	2363 / 2.48	2449 / 2.89	2534 / 3.33	2619 / 3.79						
4430	2392 / 2.26	2471 / 2.65	2549 / 3.06	2628 / 3.49								
4800	2592 / 2.88	2665 / 3.29										

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.