

RTU2-I.50-18-FA

CFM	Static Pressure in Inches W.G.												
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500	5.000	5.500	6.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
500			1131 / 0.23	1362 / 0.38	1562 / 0.54	1736 / 0.72	1894 / 0.91	2041 / 1.12	2183 / 1.35	2304 / 1.56	2427 / 1.80	2538 / 2.03	2646 / 2.28
800		943 / 0.18	1210 / 0.33	1429 / 0.51	1619 / 0.71	1790 / 0.92	1946 / 1.15	2089 / 1.38	2222 / 1.63	2353 / 1.90	2469 / 2.16	2589 / 2.45	2694 / 2.73
1100		1085 / 0.29	1322 / 0.48	1524 / 0.69	1700 / 0.92	1861 / 1.16	2011 / 1.41	2153 / 1.69	2282 / 1.96	2407 / 2.26	2523 / 2.55	2638 / 2.87	
1400	1019 / 0.24	1248 / 0.44	1457 / 0.68	1641 / 0.93	1806 / 1.19	1958 / 1.47	2099 / 1.75	2233 / 2.05	2357 / 2.36	2478 / 2.68	2593 / 3.02		
1700	1237 / 0.42	1426 / 0.67	1610 / 0.94	1776 / 1.23	1930 / 1.53	2073 / 1.85	2208 / 2.17	2332 / 2.50	2453 / 2.84	2568 / 3.20	2677 / 3.56		
2000	1456 / 0.69	1616 / 0.97	1776 / 1.28	1929 / 1.62	2070 / 1.96	2203 / 2.31	2328 / 2.67	2448 / 3.04	2564 / 3.42	2670 / 3.80			
2300	1673 / 1.05	1811 / 1.36	1952 / 1.71	2091 / 2.09	2220 / 2.46	2345 / 2.86	2465 / 3.27	2578 / 3.68	2687 / 4.10				
2600	1891 / 1.51	2014 / 1.86	2138 / 2.25	2263 / 2.66	2383 / 3.08	2498 / 3.51	2610 / 3.96						
2900	2109 / 2.10	2219 / 2.48	2331 / 2.91	2443 / 3.35	2553 / 3.81	2661 / 4.29							
3200	2327 / 2.82	2426 / 3.24	2528 / 3.70	2629 / 4.18									
3500	2545 / 3.69	2636 / 4.15											

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 186726/A01-ECM-50-277-18 has an rpm range of 900 to 1950.

Motor 186726/A01-ECM-60-277-18 has an rpm range of 900 to 1950.

Motor 186730/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 186730/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 186731/A01-ECM-60-480-18 has an rpm range of 900 to 2700.