

RTU3-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000		621 / 0.15	861 / 0.35	1046 / 0.58	1203 / 0.83	1342 / 1.11	1468 / 1.40	1582 / 1.71	1692 / 2.05
1600		665 / 0.22	887 / 0.47	1069 / 0.76	1224 / 1.07	1362 / 1.40	1486 / 1.74	1600 / 2.11	1708 / 2.50
2200	542 / 0.07	749 / 0.30	934 / 0.60	1102 / 0.94	1251 / 1.30	1386 / 1.69	1509 / 2.10	1622 / 2.52	1730 / 2.97
2800	689 / 0.15	858 / 0.42	1010 / 0.75	1155 / 1.13	1292 / 1.55	1420 / 1.99	1538 / 2.46	1650 / 2.94	1754 / 3.44
3400	837 / 0.26	980 / 0.59	1109 / 0.96	1233 / 1.37	1354 / 1.83	1469 / 2.31	1580 / 2.83	1686 / 3.36	1787 / 3.92
4000	984 / 0.43	1110 / 0.81	1222 / 1.22	1329 / 1.67	1435 / 2.16	1538 / 2.68	1639 / 3.23	1736 / 3.81	1831 / 4.42
4600	1132 / 0.65	1243 / 1.08	1343 / 1.54	1438 / 2.03	1532 / 2.55	1624 / 3.11	1714 / 3.70	1803 / 4.32	
5200	1280 / 0.94	1380 / 1.43	1470 / 1.93	1556 / 2.46	1640 / 3.03	1722 / 3.62	1804 / 4.24		
5800	1427 / 1.31	1518 / 1.85	1601 / 2.40	1680 / 2.98	1756 / 3.58	1831 / 4.21			
6400	1575 / 1.76	1658 / 2.35	1735 / 2.96	1807 / 3.58					
7000	1722 / 2.30	1799 / 2.95							

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 500 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 500 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 500 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 500 to 1870.