

**RTU3-E.1006-22-FA**

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3400	892 / 0.38	1028 / 0.72	1153 / 1.10	1276 / 1.53	1395 / 2.00	1510 / 2.50	1621 / 3.03	1726 / 3.58	1827 / 4.15
3760	987 / 0.51	1111 / 0.88	1226 / 1.29	1337 / 1.74	1447 / 2.24	1552 / 2.76	1659 / 3.32	1759 / 3.90	1857 / 4.50
4120	1081 / 0.68	1196 / 1.07	1302 / 1.51	1404 / 1.99	1505 / 2.50	1604 / 3.05	1702 / 3.63	1798 / 4.24	
4480	1176 / 0.87	1283 / 1.30	1381 / 1.76	1476 / 2.27	1569 / 2.81	1662 / 3.38	1753 / 3.98	1843 / 4.61	
4840	1270 / 1.09	1370 / 1.55	1461 / 2.05	1550 / 2.58	1637 / 3.14	1724 / 3.74	1809 / 4.37		
5200	1364 / 1.36	1458 / 1.85	1544 / 2.37	1628 / 2.93	1709 / 3.52	1790 / 4.14	1870 / 4.78		
5560	1459 / 1.66	1547 / 2.18	1629 / 2.74	1707 / 3.32	1784 / 3.93	1860 / 4.58			
5920	1553 / 2.00	1637 / 2.56	1714 / 3.14	1788 / 3.75	1861 / 4.39				
6280	1648 / 2.39	1727 / 2.98	1800 / 3.59						
6640	1742 / 2.82	1817 / 3.45							
7000	1837 / 3.31								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.