

RTU3-E.154-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000			872 / 0.36	1057 / 0.60	1215 / 0.86	1355 / 1.14	1481 / 1.44	1600 / 1.77	1709 / 2.11
1600			907 / 0.50	1088 / 0.79	1242 / 1.11	1379 / 1.44	1504 / 1.80	1618 / 2.18	1726 / 2.58
2200			961 / 0.65	1128 / 1.00	1278 / 1.37	1412 / 1.77	1534 / 2.19	1648 / 2.62	1753 / 3.07
2800		896 / 0.50	1046 / 0.84	1189 / 1.23	1326 / 1.66	1453 / 2.12	1572 / 2.59	1683 / 3.09	1787 / 3.60
3400	892 / 0.38	1028 / 0.72	1153 / 1.10	1276 / 1.53	1395 / 2.00	1510 / 2.50	1621 / 3.03	1726 / 3.58	1827 / 4.15
4000	1050 / 0.62	1168 / 1.00	1276 / 1.43	1381 / 1.90	1485 / 2.41	1587 / 2.95	1687 / 3.53	1785 / 4.13	
4600	1207 / 0.94	1311 / 1.38	1407 / 1.85	1500 / 2.36	1591 / 2.91	1682 / 3.49	1771 / 4.11	1859 / 4.74	
5200	1364 / 1.36	1458 / 1.85	1544 / 2.37	1628 / 2.93	1709 / 3.52	1790 / 4.14	1870 / 4.78		
5800	1522 / 1.88	1606 / 2.43	1686 / 3.00	1761 / 3.60	1835 / 4.23				
6400	1679 / 2.53	1757 / 3.13	1829 / 3.75						

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.