

RTU3-E.302-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1150			879 / 0.39	1064 / 0.64	1221 / 0.92	1359 / 1.21	1486 / 1.53	1602 / 1.87	1711 / 2.22
1735			916 / 0.53	1095 / 0.83	1249 / 1.16	1386 / 1.51	1510 / 1.89	1625 / 2.28	1732 / 2.69
2320			976 / 0.68	1138 / 1.04	1286 / 1.43	1419 / 1.84	1542 / 2.27	1655 / 2.72	1759 / 3.17
2905		918 / 0.53	1063 / 0.88	1203 / 1.28	1336 / 1.72	1462 / 2.18	1580 / 2.67	1690 / 3.17	1793 / 3.69
3490	916 / 0.41	1049 / 0.75	1171 / 1.14	1291 / 1.58	1407 / 2.06	1521 / 2.57	1630 / 3.10	1735 / 3.66	1834 / 4.23
4075	1070 / 0.65	1185 / 1.05	1292 / 1.48	1396 / 1.96	1498 / 2.47	1598 / 3.02	1697 / 3.60	1793 / 4.20	
4660	1223 / 0.98	1326 / 1.42	1421 / 1.90	1512 / 2.42	1602 / 2.97	1692 / 3.55	1781 / 4.17	1868 / 4.81	
5245	1376 / 1.39	1469 / 1.89	1555 / 2.41	1637 / 2.97	1719 / 3.57	1799 / 4.19			
5830	1530 / 1.91	1614 / 2.46	1692 / 3.04	1767 / 3.64	1841 / 4.27				
6415	1683 / 2.55	1760 / 3.15	1833 / 3.77						
7000	1837 / 3.31								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.