

RTU3-E.454-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			900 / 0.47	1082 / 0.76	1237 / 1.06	1375 / 1.39	1499 / 1.74	1615 / 2.11	1722 / 2.50
2100			950 / 0.62	1120 / 0.96	1271 / 1.33	1406 / 1.71	1528 / 2.12	1642 / 2.54	1749 / 2.99
2700		875 / 0.47	1029 / 0.81	1177 / 1.19	1316 / 1.61	1445 / 2.05	1565 / 2.53	1676 / 3.01	1781 / 3.51
3300	866 / 0.35	1006 / 0.67	1134 / 1.05	1260 / 1.48	1382 / 1.94	1499 / 2.43	1612 / 2.96	1719 / 3.50	1820 / 4.06
3900	1024 / 0.57	1144 / 0.95	1255 / 1.37	1363 / 1.84	1469 / 2.34	1573 / 2.87	1675 / 3.44	1774 / 4.03	1870 / 4.64
4500	1181 / 0.88	1287 / 1.31	1385 / 1.78	1479 / 2.28	1573 / 2.82	1665 / 3.40	1756 / 4.00	1846 / 4.64	
5100	1338 / 1.28	1433 / 1.76	1521 / 2.28	1606 / 2.83	1689 / 3.41	1771 / 4.02	1853 / 4.66		
5700	1496 / 1.79	1582 / 2.32	1662 / 2.89	1738 / 3.48	1814 / 4.11				
6300	1653 / 2.41	1732 / 3.00	1805 / 3.62						
6900	1811 / 3.17								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.