

RTU3-E.456-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			900 / 0.47	1082 / 0.76	1237 / 1.06	1375 / 1.39	1499 / 1.74	1615 / 2.11	1722 / 2.50
2050			945 / 0.61	1117 / 0.94	1268 / 1.30	1403 / 1.69	1526 / 2.09	1640 / 2.51	1745 / 2.94
2600		855 / 0.44	1014 / 0.77	1166 / 1.15	1308 / 1.56	1438 / 2.00	1559 / 2.46	1670 / 2.93	1775 / 3.42
3150	827 / 0.30	972 / 0.62	1106 / 0.98	1237 / 1.40	1364 / 1.85	1484 / 2.34	1599 / 2.85	1707 / 3.37	1809 / 3.92
3700	971 / 0.49	1097 / 0.85	1213 / 1.26	1327 / 1.71	1437 / 2.19	1547 / 2.72	1652 / 3.27	1754 / 3.85	1851 / 4.44
4250	1115 / 0.74	1227 / 1.15	1330 / 1.60	1430 / 2.08	1528 / 2.61	1625 / 3.17	1721 / 3.76	1813 / 4.37	
4800	1260 / 1.07	1360 / 1.52	1452 / 2.01	1542 / 2.54	1629 / 3.10	1717 / 3.70	1802 / 4.32		
5350	1404 / 1.48	1495 / 1.98	1579 / 2.52	1660 / 3.09	1740 / 3.68	1818 / 4.31			
5900	1548 / 1.98	1632 / 2.54	1709 / 3.12	1784 / 3.73	1857 / 4.37				
6450	1692 / 2.59	1770 / 3.19	1841 / 3.82						
7000	1837 / 3.31								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.