

RTU3-E.602-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900			930 / 0.57	1106 / 0.89	1259 / 1.24	1395 / 1.61	1519 / 1.99	1632 / 2.40	1738 / 2.82
2410		817 / 0.39	987 / 0.71	1147 / 1.07	1292 / 1.47	1425 / 1.89	1547 / 2.33	1660 / 2.78	1763 / 3.24
2920		922 / 0.54	1066 / 0.89	1205 / 1.29	1338 / 1.73	1463 / 2.19	1580 / 2.68	1691 / 3.18	1795 / 3.71
3430	900 / 0.39	1035 / 0.73	1159 / 1.11	1281 / 1.55	1399 / 2.02	1514 / 2.52	1624 / 3.06	1729 / 3.61	1829 / 4.18
3940	1034 / 0.59	1153 / 0.97	1263 / 1.40	1370 / 1.86	1475 / 2.37	1579 / 2.90	1680 / 3.48	1778 / 4.07	
4450	1168 / 0.85	1275 / 1.28	1374 / 1.74	1469 / 2.24	1564 / 2.78	1657 / 3.35	1749 / 3.95	1840 / 4.58	
4960	1301 / 1.18	1399 / 1.65	1489 / 2.15	1576 / 2.69	1661 / 3.26	1745 / 3.87	1829 / 4.50		
5470	1435 / 1.58	1525 / 2.09	1607 / 2.64	1687 / 3.22	1765 / 3.83	1842 / 4.47			
5980	1569 / 2.06	1651 / 2.62	1728 / 3.21	1802 / 3.83					
6490	1703 / 2.64	1780 / 3.25	1851 / 3.88						
7000	1837 / 3.31								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.