

RTU3-I.150-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000			894 / 0.39	1075 / 0.63	1232 / 0.89	1370 / 1.18	1497 / 1.49	1613 / 1.81	1721 / 2.15
1500			947 / 0.54	1122 / 0.83	1272 / 1.14	1406 / 1.48	1527 / 1.83	1641 / 2.21	1746 / 2.60
2000		831 / 0.42	1018 / 0.73	1181 / 1.08	1325 / 1.44	1455 / 1.82	1574 / 2.23	1684 / 2.65	1787 / 3.09
2500		947 / 0.63	1107 / 0.99	1253 / 1.38	1390 / 1.80	1514 / 2.24	1629 / 2.69	1736 / 3.17	1837 / 3.66
3000	937 / 0.56	1076 / 0.91	1213 / 1.32	1343 / 1.76	1468 / 2.23	1584 / 2.72	1694 / 3.24	1797 / 3.76	
3500	1093 / 0.88	1212 / 1.29	1331 / 1.74	1446 / 2.23	1558 / 2.75	1666 / 3.30	1769 / 3.86	1867 / 4.44	
4000	1249 / 1.32	1353 / 1.77	1458 / 2.27	1561 / 2.81	1661 / 3.38	1760 / 3.98	1855 / 4.59		
4500	1404 / 1.87	1498 / 2.38	1591 / 2.93	1683 / 3.51	1774 / 4.13	1863 / 4.77			
5000	1561 / 2.57	1645 / 3.13	1728 / 3.72	1812 / 4.36					
5500	1717 / 3.42	1793 / 4.03	1869 / 4.68						

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.