

RTU3-I.150HE-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000			901 / 0.40	1082 / 0.64	1238 / 0.90	1376 / 1.19	1502 / 1.50	1618 / 1.83	1727 / 2.17
1450			956 / 0.54	1128 / 0.83	1279 / 1.14	1412 / 1.47	1534 / 1.83	1646 / 2.19	1753 / 2.59
1900		837 / 0.43	1026 / 0.73	1189 / 1.07	1332 / 1.43	1460 / 1.80	1579 / 2.20	1689 / 2.62	1792 / 3.05
2350		946 / 0.63	1112 / 0.98	1261 / 1.37	1396 / 1.77	1520 / 2.20	1634 / 2.64	1741 / 3.10	1842 / 3.58
2800	925 / 0.55	1067 / 0.90	1210 / 1.30	1346 / 1.73	1471 / 2.19	1589 / 2.66	1698 / 3.15	1802 / 3.67	
3250	1073 / 0.86	1195 / 1.25	1320 / 1.70	1441 / 2.18	1557 / 2.69	1667 / 3.21	1771 / 3.75	1870 / 4.31	
3700	1222 / 1.27	1328 / 1.71	1437 / 2.20	1546 / 2.72	1653 / 3.28	1754 / 3.85	1852 / 4.44		
4150	1370 / 1.79	1464 / 2.28	1562 / 2.81	1659 / 3.38	1756 / 3.98	1850 / 4.61			
4600	1519 / 2.44	1603 / 2.97	1691 / 3.55	1779 / 4.16	1866 / 4.81				
5050	1667 / 3.23	1744 / 3.81	1823 / 4.43						
5500	1816 / 4.17								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.