

RTU3-I.200-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100			886 / 0.39	1069 / 0.64	1225 / 0.91	1365 / 1.21	1491 / 1.52	1606 / 1.85	1716 / 2.21	1818 / 2.57
1650			930 / 0.54	1107 / 0.84	1260 / 1.16	1395 / 1.51	1518 / 1.87	1632 / 2.26	1739 / 2.66	1837 / 3.07
2200		812 / 0.39	993 / 0.71	1157 / 1.06	1303 / 1.44	1435 / 1.84	1556 / 2.26	1668 / 2.70	1773 / 3.16	
2750		929 / 0.57	1080 / 0.93	1224 / 1.33	1359 / 1.76	1484 / 2.22	1601 / 2.69	1710 / 3.19	1813 / 3.70	
3300	929 / 0.48	1059 / 0.82	1186 / 1.22	1311 / 1.66	1431 / 2.14	1546 / 2.65	1657 / 3.18	1761 / 3.72	1860 / 4.29	
3850	1084 / 0.76	1196 / 1.15	1305 / 1.59	1413 / 2.08	1520 / 2.60	1624 / 3.15	1726 / 3.73	1823 / 4.32		
4400	1239 / 1.14	1337 / 1.58	1434 / 2.06	1529 / 2.59	1623 / 3.15	1717 / 3.74	1808 / 4.36			
4950	1393 / 1.62	1481 / 2.11	1567 / 2.64	1653 / 3.21	1737 / 3.81	1821 / 4.44				
5500	1548 / 2.22	1628 / 2.76	1705 / 3.34	1782 / 3.94	1859 / 4.59					
6050	1703 / 2.95	1775 / 3.54	1846 / 4.17							
6600	1858 / 3.83									

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.